



## ACE-TUF® Heavy Duty Industrial Wheel Assemblies with Solid Rubber Tires

Specially formulated reprocessed rubber for industrial wheel applications, only ACE-TUF® polyolefin wheel center tire combinations can withstand load ratings up to 500 lbs., depending on bearing and application.

Available with ball bearings for easier rolling, acetal bearings (plastic) for applications where rust prevention is important, or sintered metal bearings for 500 lb. load ratings in applications where rust is not a concern.

ACE-TUF® hubs are available in a 2 1/4" offset, ideal for material handling applications. Also available in 2 1/2" and 3 1/4" symmetrical hubs for caster wheel applications.

**5-RIB TREAD DESIGN ON ALL TIRES.**

**STANDARD WHEEL COLORS:** White, Off-White, Silver, Gray (Set-up charge for colors other than above).

**AVAILABLE IN SIZES:** 8 x 2.50" — Tire No. 3855-8  
10 x 2.75" — Tire No. 3845-10  
10 x 4.00" — Tire No. 3875-10  
12 x 3.00" — Tire No. 3865-12

**LOAD RATING:** (All wheels are load rated according to the bearing configuration.)  
Ball Bearings — Load Rating: 300 lbs.  
Acetal Bushings — Load Rating: 500 lbs.  
Sintered Metal Bushings — Load Rating: 500 lbs.

All dimensions are nominal.

**BORES AVAILABLE:** Ball Bearings: 1/2", 5/8", 3/4", & 20mm  
Acetal Bushings: 1/2", 5/8", 3/4"  
Sintered Bushings: 1/2", 5/8", 3/4", 1"  
12mm, 14mm & 20mm

**HUB LENGTHS:** A - 2-1/4" Offset (Not Available on 12" x 3" Wheels)  
B - 2-1/2" Symmetrical  
C - 3-1/4" Extended Hub-Symmetrical

Minimum Release: 1 Pallet

**AVERAGE PALLET QUANTITIES:** (approx.)

HUB LENGTH	8 X 2.50	10 X 2.75	10 X 4	12 X 3
2-1/4" Hub	440	248	160	N/A
2-1/2" Hub	400	248	160	144
3-1/4" Hub	400	200	160	144
Average Pallet Weight:	1445 lbs.	1466 lbs.	1466 lbs.	1280 lbs.

**if it rolls, we have it!**  
**SERVICE CASTER**

**SERVICE CASTER CORPORATION Call 1-800-215-8220**