



S2053-GSL11-SRG-BB-TG-DLB

FEATURES

- KINGPIN:** 3/4" diameter heavy duty nut & bolt kingpin
- BALLS:** 1/4" diameter upper and lower race; hardened steel load bearings
- BUSHING:** Nylon, steel or ball bearings
- AXLE & NUT:** 5/16" axle & lock nut
- FINISH:** Corrosion resistant bright zinc finish
- SPECIAL:** Double brake locks wheel & swivel in any direction. Swivel lock only is also available. Custom plates & bolt hole spacing available. Custom deflections available.
- LEG SPACING:** 1 5/8"

Excellent for:

- Residential or industrial gates
- Sliding or rotating industrial doors
- Heavy duty panels
- Test facilities
- Low profile side mounted applications

Options:

- DLB** Double Locking Brake (swivel only)
- SWLB** Swivel Locking Brake (swivel only)
- TG** Thread Guards
- BB** Sealed Ball Bearings
SR, SRG & U Wheels Only
- Z** Zerk Axle & Lock Nut
- DB** Derlin Bearing
- C** Raceway Seal

Finish

Inquiries on other finishes welcome

WHEEL			CASTER			PART NUMBER	
Diameter	Tread Width	Bearing Type	Capacity Lbs.	Swivel Radius	Overall Height	Wheel Type	Swivel
3"	1 1/4"	Steel	250	2 5/8"	4 9/16"	Hard Rubber	S2033-GSL11-HR
		Steel	250			High Temp Phenolic (475°)	S2033-GSL11-HTPH
		Steel	250			Phenolic	S2033-GSL11-PH
		Plain	250			Polyolefin	S2033-GSL11-PO
		Nylon	250			ProTech Flat Tread	S2033-GSL11-PROF
		Ball	250			ProTech Flat Tread	S2033-GSL11-PROF-BB-TG
		Steel	250			Soft Rubber	S2033-GSL11-SR
		Steel	250			Soft Rubber Grey	S2033-GSL11-SRG
		Steel	250			Steel	S2033-GSL11-ST
		Nylon	250			Envirothane	S2033-GSL11-U
		Nylon	250			Envirothane Grey	S2033-GSL11-UG
4"	1 1/4"	Steel	275	3"	5 9/16"	Hard Rubber	S2043-GSL11-HR
		Steel	275			High Temp Phenolic (475°)	S2043-GSL11-HTPH
		Steel	275			Phenolic	S2043-GSL11-PH
		Ball	275			Moldon Urethane	S2043-GSL11-PLY-BB-TG
		Plain	275			Polyolefin	S2043-GSL11-1 1/2 PO
		Ball	275			ProTech Flat Tread	S2043-GSL11-PROF-BB-TG
		Nylon	275			ProTech Flat Tread	S2043-GSL11-PROF
		Steel	275			Soft Rubber	S2043-GSL11-SR
		Steel	275			Soft Rubber Grey	S2043-GSL11-SRG
		Steel	275			Steel	S2043-GSL11-ST
		Nylon	275			Envirothane	S2043-GSL11-U
Nylon	275	Envirothane Grey	S2043-GSL11-UG				
5"	1 1/4"	Steel	300	3 5/8"	6 1/16"	Hard Rubber	S2053-GSL11-HR
		Steel	300			High Temp Phenolic (475°)	S2053-GSL11-HTPH
		Plain	300			Polyolefin	S2053-GSL11-PO
		Steel	300			Phenolic	S2053-GSL11-PH
		Ball	300			Moldon Urethane	S2053-GSL11-PLY-BB-TG
		Ball	300			ProTech Flat Tread	S2053-GSL11-PROF-BB-TG
		Nylon	300			ProTech Flat Tread	S2053-GSL11-PROF
		Steel	300			Soft Rubber	S2053-GSL11-SR
		Steel	300			Soft Rubber Grey	S2053-GSL11-SRG
		Steel	300			Steel	S2053-GSL11-ST
		Nylon	300			Envirothane	S2053-GSL11-U
Nylon	300	Envirothane Grey	S2053-GSL11-UG				

Standard Deflection Characteristics:

- * Deflection Begins: 180 Lbs.
- * Deflection @ Capacity (300 Lbs.) $\frac{5}{16}$ "
- * Deflection Characteristics Can Be Customized To Any Requirements Up To 300 Lbs.

