


Series: LKRXA-VPA, BKRXA-VPA

Stainless steel light duty swivel and fixed castors with bolt hole fitting

 60 - 100 kg



Brackets: LKRXA/BKRXA Series - Pressed from high-quality, chromium-nickel stainless steel (material No. 1.4301/AISI 304), swivel bracket with double ball bearing in the swivel head, strong central kingpin and bolted wheel axle. All metal parts are stainless steel and brackets are vibration-ground finished.
Detailed description: Page 67 and 76.

Wheels: VPA Series - Tyres: Solid rubber, colour grey, non-marking, 80° shore A. Rims: Made of high-quality nylon, shock and impact-resistant, corrosion-resistant, plain bearing, colour black.
Detailed description: Page 92 and 30.

Swivel castors		Fixed castors		Swivel castors with "stop-fix" brake		Wheel Ø	Tyre width	Load capacity	Bearing version	Total height	Plate Ø	Bolt hole Ø	Offset swvl castor
Ref. No.	Ref. No.	Ref. No.	Ref. No.	Ref. No.	Ref. No.	[mm]	[mm]	[kg]		[mm]	[mm]	[mm]	[mm]
LKRXA-VPA 80G	BKRXA-VPA 80G	LKRXA-VPA 80G-FI	LKRXA-VPA 80G-11-FI			80	25	60	Plain bearing	108	57	13	40
LKRXA-VPA 80G-11						80	25	60	Plain bearing	108	57	11	40
LKRXA-VPA 101G	BKRXA-VPA 101G	LKRXA-VPA 101G-FI	LKRXA-VPA 101G-11-FI			100	32	90	Plain bearing	133	57	13	40
LKRXA-VPA 101G-11						100	32	90	Plain bearing	133	57	11	40
LKRXA-VPA 125G	BKRXA-VPA 125G	LKRXA-VPA 125G-FI	LKRXA-VPA 125G-11-FI			125	25	80	Plain bearing	158	57	13	40
LKRXA-VPA 125G-11						125	25	80	Plain bearing	158	57	11	40
LKRXA-VPA 126G	BKRXA-VPA 126G	LKRXA-VPA 126G-FI	LKRXA-VPA 126G-11-FI			125	32	100	Plain bearing	158	57	13	40
LKRXA-VPA 126G-11						125	32	100	Plain bearing	158	57	11	40

