

# Polytech Series

## Thermoplastic Rubber

Capacity 150 - 800



Polytech Thermoplastic Rubber wheels are manufactured with a non-marking thermoplastic rubber tread, chemically bonded to a polyolefin core. This combination provides smooth rolling, impact resistant wheels.

### Features

- Non Marking
- Light Weight
- Quiet Rolling
- Easily Cleaned
- Highly Impact Resistant
- Unaffected By Most Chemicals
- Temperature Range -20°F / +180°F
- Durometer 80 Shore A

### Options

- Metal Washers
- Sealed Precision Bearings
- Available In Various Colors

Wheel Diameter	Tread Width	Load Capacity	Bore Size	Hub Length	Bearing Type	Offset Hub	Part Number	Shipping Weight
4	1	150	5/16	1 1/8	Plain	No	90-06-001-11	0.3
	1 3/8	200	1/2	1 1/2	Plain	No	90-06-037-11	0.5
	2	350	3/4	2 3/16	Plain	No	90-06-012-11	1
			3/4	2 3/16	Delrin	No	90-56-022-11	
			3/4	2 3/16	Roller	No	90-26-022-11	
1 3/16	2 3/16	Plain	No	90-06-022-11				
5	2	375	3/4	2 3/16	Plain	No	90-06-013-11	
			3/4	2 3/16	Delrin	No	90-56-023-11	
			3/4	2 3/16	Roller	No	90-26-023-11	
			1 3/16	2 3/16	Plain	No	90-06-023-11	
6	2	600	3/4	2 3/16	Plain	No	90-06-014-11	1.75
			3/4	2 3/16	Delrin	No	90-56-024-11	
			3/4	2 3/16	Roller	No	90-26-024-11	
			1 3/16	2 3/16	Plain	No	90-06-024-11	
8	1 5/8	500	5/8	1 1/2	Plain	Yes	90-06-021-11	1.8
			5/8	2	Plain	No	90-06-016-11	
			3/4	1 1/2	Plain	Yes	90-06-029-11	
			3/4	2	Plain	No	90-06-015-11	
	2	675	1/2	2 3/16	Delrin	No	90-46-025-11	2
			3/4	2 3/16	Plain	No	90-06-008-11	
			3/4	2 3/16	Delrin	No	90-56-025-11	
			3/4	2 3/16	Roller	No	90-26-025-11	