

### 3I series

- Corrosion Resistant for wash-down applications
- Medical Equipment
- Electronic Equipment
- Institutional Furniture



#### "3I" Series Industrial Series Swivel Casters featuring Total Lock Braking

Wheel diameter Inch / (mm)	Caster Width Inch (mm)	Load Rating <sup>2</sup> Lbs. / Kg.	Wheel Color	Caster Finish	Wheel Material	Overall Height <sup>1</sup> (Reference only)	Mounting Options <sup>3</sup>	Part Numbers
<b>Swivel Only</b>								
4" (100mm)	1-1/4" (32mm)	125 lbs. (57 Kg.)	Light Grey	White/ Grey	Thermo- Plastic Rubber	5-7/8" (148mm)	Plate	Special Order
						5-3/4" (145mm)	Threaded	Special Order
						5-3/8" (137mm)	Round Stem with Mounting hole	Special Order
See Icons below for options								
5" (125mm)	1-3/8" (35mm)	140 lbs. (63 Kg.)	Light Grey	White / Grey	Thermo- Plastic Rubber	6-13/16" (172mm)	Plate	Special Order
						6-3/4" (170mm)	Threaded	Special Order
						6-7/16" (162mm)	Round Stem with Mounting hole	Special Order
See Icons below for options								
<b>Swivel with Total Lock Braking System</b>								
4" (100mm)	1-1/4" (32mm)	125 lbs. (57 Kg.)	Light Grey	White / Grey	Thermo- Plastic Rubber	5-7/8" (148mm)	Plate	Special Order
						5-3/4" (145mm)	Threaded	Special Order
						5-3/8" (137mm)	Round Stem with Mounting hole	Special Order
See Icons below for options								
5" (125mm)	1-3/8" (35mm)	140 lbs. (63 Kg.)	Light Grey	White / Grey	Thermo- Plastic Rubber	6-13/16" (172mm)	Plate	Special Order
						6-3/4" (170mm)	Threaded	Special Order
						6-7/16" (162mm)	Round Stem with Mounting hole	Special Order
See Icons below for options								

Additional colors available - Contact factory for details    Additional finishes available - Contact factory for details    Additional mounting options are available - Contact factory for specifications

1. Overall heights are estimated. For exact dimensions and tolerances, please contact factory and request samples to determine fitness for use in your application.

2. Load ratings are estimated. Always load test your caster to your required application to determine fitness for use.

3. Please refer to pages 37 & 40 for specific lengths and mounting options.

## 3N series

- Corrosion Resistant for wash-down applications
- Medical Equipment
- Electronic Equipment
- Institutional Furniture



### "3N" Series Swivel Casters featuring Total Lock Braking and European Styling

Wheel diameter Inch / (mm)	Caster Width Inch (mm)	Load Rating <sup>2</sup> Lbs. / Kg.	Wheel Color	Caster Finish	Wheel Material	Overall Height <sup>1</sup> (Reference only)	Mounting Options <sup>3</sup>	Part Numbers
<b>Swivel Only</b>								
3" (75mm)	1-1/8" (28mm)	110 lbs. (50 Kg.)	Light Grey	White / Grey	Thermo- plastic Rubber	5-1/8" (130mm)	Plate	Special Order
						4-13/16"(123mm)	Threaded	
						4-1/2" (115mm)	Round Stem with Mounting hole	
See Icons below for options								
4" (100mm)	1-3/16" (30mm)	125 lbs. (57 Kg.)	Light Grey	White/ Grey	Thermo- plastic Rubber	6-5/16" (160mm)	Plate	Special Order
						5-15/16"(151mm)	Threaded	
						5-5/8" (143mm)	Round Stem with Mounting hole	
See Icons below for options								
5" (125mm)	1-1/4" (32mm)	140 lbs. (63 Kg.)	Light Grey	White / Grey	Thermo- plastic Rubber	7-1/4" (185mm)	Plate	Special Order
						7" (178mm)	Threaded	
						6-5/8" (168mm)	Round Stem with Mounting hole	
See Icons below for options								
<b>Swivel with Total Lock Braking System</b>								
3" (75mm)	1-1/8" (28mm)	110 lbs. (50 Kg.)	Light Grey	White / Grey	Thermo- plastic Rubber	5-1/8" (130mm)	Plate	Special Order
						4-13/16"(123mm)	Threaded	
						4-1/2" (115mm)	Round Stem with Mounting hole	
See Icons below for options								
4" (100mm)	1-3/16" (30mm)	125 lbs. (57 Kg.)	Light Grey	White / Grey	Thermo- plastic Rubber	6-5/16" (160mm)	Plate	Special Order
						5-15/16"(151mm)	Threaded	
						5-5/8" (143mm)	Round Stem with Mounting hole	
See Icons below for options								
5" (125mm)	1-1/4" (32mm)	140 lbs. (63 Kg.)	Light Grey	White / Grey	Thermo- plastic Rubber	7-1/4" (185mm)	Plate	Special Order
						7" (178mm)	Threaded	
						6-5/8" (168mm)	Round Stem with Mounting hole	
See Icons below for options								
<b>Swivel with Directional Lock Braking System</b>								
3" (75mm)	1-1/8" (28mm)	110 lbs. (50 Kg.)	Light Grey	White / Grey	Thermo- plastic Rubber	5-1/8" (130mm)	Plate	Special Order
						4-13/16"(123mm)	Threaded	
						4-1/2" (115mm)	Round Stem with Mounting hole	
See Icons below for options								
4" (100mm)	1-3/16" (30mm)	125 lbs. (57 Kg.)	Light Grey	White / Grey	Thermo- plastic Rubber	6-5/16" (160mm)	Plate	Special Order
						5-15/16"(151mm)	Threaded	
						5-5/8" (143mm)	Round Stem with Mounting hole	
See Icons below for options								
5" (125mm)	1-1/4" (32mm)	140 lbs. (63 Kg.)	Light Grey	White / Grey	Thermo- plastic Rubber	7-1/4" (185mm)	Plate	Special Order
						7" (178mm)	Threaded	
						6-5/8" (168mm)	Round Stem with Mounting hole	
See Icons below for options								

Additional colors available - Contact factory for details  
 Additional finishes available - Contact factory for details  
 Additional mounting options are available - Contact factory for specifications

1. Overall heights are estimated. For exact dimensions and tolerances, please contact factory and request samples to determine fitness for use in your application.
2. Load ratings are estimated. Always load test your caster to your required application to determine fitness for use.
3. Please refer to pages 37 & 40 for specific lengths and mounting options.