



Pneumatic wheels

- **wheelbarrows**
- **dollies**
- **sanding gear**
- **boat trailers**
- **light trailers for outdoor use**

Manner pneumatic wheels are intended for equipment which needs a flexible and soft rolling wheel. The highest rated speed is four kilometres per hour. Split rims make wheel maintenance easier.

Wheels are available either for through or single ended axle.

Pneumatic wheels



117

LF RIM FOR THROUGH AXLE

Code	bottom ϕ / inner width	suitable tyre size					
LF-101/54	101/54	3.00-4	70	20	•	200	0,94
LF-151/62	151/62	4.00-6	70	25	•	360	1,16
LF-201/64	201/64	4.00-8	80	25	•	550	2,13
LF-201/76	201/76	5.00-8	90	30	•	1000	3,92



118

LFU RIM FOR SINGLE ENDED AXLE

Code	bottom ϕ / inner width	suitable tyre size					
LFU-101/54	101/54	3.00-4	70	25	•	200	0,89
LFU-151/62	151/62	4.00-6	70	25	•	360	1,17
LFU-201/64	201/64	4.00-8	80	25	•	550	2,14
LFU-201/76	201/76	5.00-8	90	30/35	•	1000	3,97



119

LTI WHEEL FOR THROUGH AXLE

IM pressed steel centre + pneumatic rubber tyre, ball bearing (unsealed). IM/D pressed steel centre + pneumatic rubber tyre, plain bearing.

Code							
LTI-225 IM/2	225 2.00-4	50	50	20	-	•	135 1,17
LTI-260 IM/4	266	86	70	20	-	•	200 2,01
LTI-260 IM/4/D	3.00-4	86	70	20	•	-	200 1,88
LTI-310 IM/4	295	104	70	20	-	•	250 2,32
LTI-310 IM/4/D	4.00-4	104	70	20	•	-	250 2,19
LTI-360 IM/4	350	105	70	25	-	•	300 2,55
LTI-360 IM/4/D	4.00-6	105	70	20	•	-	240 2,47
LTI-420 IM/4	400	105	80	25	-	•	310 3,42
LTI-420 IM/4/D	4.00-8	105	80	20	•	-	270 3,43
LTI-465 IM/10	460 5.00-8	151	90	30	-	•	415 5,00



120

LTK WHEEL WITH THROUGH AXLE

IM pressed steel centre + pneumatic rubber tyre, ball bearing (unsealed). IM/D pressed steel centre + pneumatic rubber tyre, plain bearing.

Code							
LTK-260 IM/4	266	86	300	20	-	•	200 2,72
LTK-260 IM/4/D	3.00-4	86	300	20	•	-	200 2,61
LTK-310 IM/4	295	104	300	20	-	•	250 3,11
LTK-310 IM/4/D	4.00-4	104	300	20	•	-	250 2,97
LTK-360 IM/4	350	105	300	25	-	•	300 3,71
LTK-360 IM/4/D	4.00-6	105	300	20	•	-	240 3,22
LTK-420 IM/4	400	105	300	25	-	•	310 4,74
LTK-420 IM/4/D	4.00-8	105	300	20	•	-	270 4,29
LTK-465 IM/10	460 5.00-8	151	300	30	-	•	415 10,98

Pneumatic wheels

LТУ WHEEL FOR SINGLE-ENDED AXLE

IM pressed steel centre + pneumatic rubber tyre, ball bearing (unsealed). IM/D pressed steel centre + pneumatic rubber tyre, plain bearing.

Code									
LТУ-260 IM/4	266	86	70	25	-	•	200		1,97
LТУ-260 IM/4/D	3.00-4	86	70	20	•	-	200		1,88
LТУ-310 IM/4	295	104	70	25	-	•	250		2,28
LТУ-310 IM/4/D	4.00-4	104	70	20	•	-	250		2,20
LТУ-360 IM/4	350	105	70	25	-	•	300		2,56
LТУ-360 IM/4/D	4.00-6	105	70	20	•	-	240		2,47
LТУ-420 IM/4	400	105	80	25	-	•	310		3,45
LТУ-420 IM/4/D	4.00-8	105	80	20	•	-	270		3,36
LТУ-465 IM/10	460	151	90	30/35	-	•	415		
	5.00-8								



121

LTKU WHEEL WITH SINGLE-ENDED AXLE

IM pressed steel centre + pneumatic rubber tyre, ball bearing (unsealed). IM/D pressed steel centre + pneumatic rubber tyre, plain bearing.

Code									
LTKU-260 IM/4	266	86	250	25	-	•	200		2,76
LTKU-260 IM/4/D	3.00-4	86	250	20	•	-	200		2,43
LTKU-310 IM/4	295	104	250	25	-	•	250		3,28
LTKU-310 IM/4/D	4.00-4	104	250	20	•	-	250		2,85
LTKU-360 IM/4	350	105	250	25	-	•	300		3,52
LTKU-360 IM/4/D	4.00-6	105	250	20	•	-	240		3,09
LTKU-420 IM/4	400	105	250	25	-	•	310		4,55
LTKU-420 IM/4/D	4.00-8	105	250	20	•	-	270		4,12
LTKU-465 IM/10	460	151	350	40	-	•	415		12,15
	5.00-8								



122

LТУ WHEEL FOR SINGLE-ENDED AXLE

PK polypropylene centre + solid-rubber tyre, plain bearing. KK steel plate centre + solid rubber tyre, ball bearing (unsealed).

Code								Sh A	
LТУ-200 PK ¹⁾	200	50	65	20	•	-	205	85	1,62
LТУ-200 KK ^{1)*)}	200	50	60	20	-	•	205	85	1,93
LТУ-250 PK	250	60	75	20	•	-	250	85	3,64
LТУ-250 KK	250	60	70	25	-	•	250	85	4,67

¹⁾ Available furnished with a grey tyre.

^{*)} Available furnished with a conductive tyre.



123

LTKU WHEEL WITH SINGLE-ENDED AXLE

PK polypropylene centre + solid-rubber tyre, plain bearing. KK steel plate centre + solid rubber tyre, ball bearing (unsealed).

Code								Sh A	
LTKU-200 PK ¹⁾	200	50	175	20	•	-	205	85	1,94
LTKU-200 KK ^{1)*)}	200	50	175	20	-	•	205	85	2,37
LTKU-250 PK	250	60	250	20	•	-	250	85	3,08
LTKU-250 KK	250	60	250	25	-	•	250	85	4,60

¹⁾ Available furnished with a grey tyre.

^{*)} Available furnished with a conductive tyre.



124

Pneumatic wheels



125

LTI WHEEL FOR THROUGH AXLE

TI/R pressed steel centre + pneumatic rubber tyre, roller bearing. TI pressed steel centre + pneumatic rubber tyre, plain bearing.

Code								
LTI-3.00-4 TI/4	266	86	75	20	•	-	200	1,19
LTI-3.00-4 TI/R/4	3.00-4	86	75	20	-	•	200	1,20
LTI-4.00-4 TI/4	295	104	75	20	•	-	250	1,98
LTI-4.00-4 TI/R/4	4.00-4	104	75	20	-	•	250	1,86
LTI-4.00-6 TI/4	350	105	75	20	•	-	250	1,75
LTI-4.00-6 TI/R/4	4.00-6	105	75	20	-	•	250	1,72
LTI-4.00-8 TI/4	400	105	75	20	•	-	300	2,18
LTI-4.00-8 TI/R/4	4.00-8	105	75	20	-	•	300	2,65



126

LTI WHEEL FOR THROUGH AXLE

MI plastic centre + pneumatic rubber tyre, plain bearing.

Code							
LTI-3.00-4 MI/4	266	86	75	20	•	200	1,14
LTI-4.00-4 MI/4	295	104	75	20	•	200	1,44
LTI-4.00-6 MI/4	350	105	80	20	•	200	1,80
LTI-4.00-8 MI/4	400	105	65	20	•	250	2,38

TYRE + TUBE

Code				
TYRE + TUBE 3.00-4 4PR	266	86	200	1,07
TYRE + TUBE 4.00-4 4PR	295	104	250	1,38
TYRE + TUBE 4.00-6 4PR	350	105	300	1,37
TYRE + TUBE 4.00-8 4PR	400	105	310	1,32

NOTE! Pneumatic wheels' patterning may differ from those illustrated.

Ask our distributor in your country for more information – see page 79.