

Chrome Hospital

Call Toll Free **1-800-215-8220** to Order Casters or for More Information.



Features

- Chrome Plated Finish
- Dual Ball Swivel Raceways for added strength
- Total Lock Brake models lock both swivel and wheel
- Directional lock models lock swivel only (helps with steering)
- Precision ball bearings in wheels for easier rollability
- Wheels have full plastic thread guards for added protection

Applications

- Food Service
- Case Carts
- Hospital Equipment
- Institutional Equipment
- Medical Equipment



Total Lock
Change "SW" to "TL". Red sticker on pedal.

Direction Lock
Change "SW" to "DL". Green sticker on pedal.

Hollow Kingpin

Wheel Diameter	Tread Width	Tread Material	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius*	Swivel Part Number
3"	1-1/4"	Thermoplastic Rubber	Precision Ball	190 lbs	4-5/16"	2-29/32"	CH-03TPP-125-SW-HK01
	1-1/4"	Polyurethane TPU	Precision Ball	190 lbs	4-5/16"	2-29/32"	CH-03PYP-125-SW-HK01
4"	1-1/4"	Thermoplastic Rubber	Precision Ball	240 lbs	5-5/16"	3-37/64"	CH-04TPP-125-SW-HK01
	1-1/4"	Polyurethane TPU	Precision Ball	240 lbs	5-5/16"	3-37/64"	CH-04PYP-125-SW-HK01
5"	1-1/4"	Thermoplastic Rubber	Precision Ball	260 lbs	6-5/16"	4-7/32"	CH-05TPP-125-SW-HK01
	1-1/4"	Polyurethane TPU	Precision Ball	260 lbs	6-5/16"	4-7/32"	CH-05PYP-125-SW-HK01
6"	1-1/4"	Thermoplastic Rubber	Precision Ball	260 lbs	7-9/32"	4-39/64"	CH-06TPP-125-SW-HK01
	1-1/4"	Polyurethane TPU	Precision Ball	260 lbs	7-9/32"	4-39/64"	CH-06PYP-125-SW-HK01

Caster is provided assembled. Change HK01 code to HKU1 for unassembled. 1/2" I.D.


HK01

*Swivel radius for total lock and direction lock models increases to: 3"=4-1/4, 4"=4-35/64, 5" & 6"=4-55/64.

Threaded Stem Models

Wheel Diameter	Tread Width	Tread Material	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius*	Swivel Part Number
3"	1-1/4"	Thermoplastic Rubber	Precision Ball	190 lbs	4-5/16"	2-29/32"	CH-03TPP-125-SW-____
	1-1/4"	Polyurethane TPU	Precision Ball	190 lbs	4-5/16"	2-29/32"	CH-03PYP-125-SW-____
4"	1-1/4"	Thermoplastic Rubber	Precision Ball	240 lbs	5-5/16"	3-37/64"	CH-04TPP-125-SW-____
	1-1/4"	Polyurethane TPU	Precision Ball	240 lbs	5-5/16"	3-37/64"	CH-04PYP-125-SW-____
5"	1-1/4"	Thermoplastic Rubber	Precision Ball	260 lbs	6-5/16"	4-7/32"	CH-05TPP-125-SW-____
	1-1/4"	Polyurethane TPU	Precision Ball	260 lbs	6-5/16"	4-7/32"	CH-05PYP-125-SW-____
6"	1-1/4"	Thermoplastic Rubber	Precision Ball	260 lbs	7-9/32"	4-39/64"	CH-06TPP-125-SW-____
	1-1/4"	Polyurethane TPU	Precision Ball	260 lbs	7-9/32"	4-39/64"	CH-06PYP-125-SW-____

TS02 TS03 TS04



Total Lock
Change "SW" to "TL". Red sticker on pedal.

Direction Lock
Change "SW" to "DL". Green sticker on pedal.

*Swivel radius for total lock and direction lock models increases to: 3"=4-1/4, 4"=4-35/64, 5" & 6"=4-55/64.




Total Lock
Change "SW"
to "TL". **Red**
sticker on pedal.

Direction Lock
Change "SW"
to "DL". **Green**
sticker on pedal.

Grip Ring Stem Models

Wheel Diameter	Tread Width	Tread Material	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius*	Swivel Part Number
3"	1-1/4"	Thermoplastic Rubber	Precision Ball	190 lbs	4-5/16"	2-29/32"	CH-03TPP-125-SW-____
	1-1/4"	Polyurethane TPU	Precision Ball	190 lbs	4-5/16"	2-29/32"	CH-03PYP-125-SW-____
4"	1-1/4"	Thermoplastic Rubber	Precision Ball	240 lbs	5-5/16"	3-37/64"	CH-04TPP-125-SW-____
	1-1/4"	Polyurethane TPU	Precision Ball	240 lbs	5-5/16"	3-37/64"	CH-04PYP-125-SW-____
5"	1-1/4"	Thermoplastic Rubber	Precision Ball	260 lbs	6-5/16"	4-7/32"	CH-05TPP-125-SW-____
	1-1/4"	Polyurethane TPU	Precision Ball	260 lbs	6-5/16"	4-7/32"	CH-05PYP-125-SW-____
6"	1-1/4"	Thermoplastic Rubber	Precision Ball	260 lbs	7-9/32"	4-39/64"	CH-06TPP-125-SW-____
	1-1/4"	Polyurethane TPU	Precision Ball	260 lbs	7-9/32"	4-39/64"	CH-06PYP-125-SW-____



*Swivel radius for total lock and direction lock models increases to: 3"=4-1/4, 4"=4-35/64, 5" & 6"=4-55/64.



Total Lock
Change "SW"
to "TL". **Red**
sticker on pedal.

Direction Lock
Change "SW"
to "DL". **Green**
sticker on pedal.

Round or Square Stem Models

Wheel Diameter	Tread Width	Tread Material	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius*	Swivel Part Number
3"	1-1/4"	Thermoplastic Rubber	Precision Ball	190 lbs	4-5/16"	2-29/32"	CH-03TPP-125-SW-____
	1-1/4"	Polyurethane TPU	Precision Ball	190 lbs	4-5/16"	2-29/32"	CH-03PYP-125-SW-____
4"	1-1/4"	Thermoplastic Rubber	Precision Ball	240 lbs	5-5/16"	3-37/64"	CH-04TPP-125-SW-____
	1-1/4"	Polyurethane TPU	Precision Ball	240 lbs	5-5/16"	3-37/64"	CH-04PYP-125-SW-____
5"	1-1/4"	Thermoplastic Rubber	Precision Ball	260 lbs	6-5/16"	4-7/32"	CH-05TPP-125-SW-____
	1-1/4"	Polyurethane TPU	Precision Ball	260 lbs	6-5/16"	4-7/32"	CH-05PYP-125-SW-____
6"	1-1/4"	Thermoplastic Rubber	Precision Ball	260 lbs	7-9/32"	4-39/64"	CH-06TPP-125-SW-____
	1-1/4"	Polyurethane TPU	Precision Ball	260 lbs	7-9/32"	4-39/64"	CH-06PYP-125-SW-____



*Swivel radius for total lock and direction lock models increases to: 3"=4-1/4, 4"=4-35/64, 5" & 6"=4-55/64.




Total Lock
Change "SW"
to "TL". **Red**
sticker on pedal.

Direction Lock
Change "SW"
to "DL". **Green**
sticker on pedal.

Expanding Adapter Stem Models

Wheel Diameter	Tread Width	Tread Material	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius*	Swivel Part Number
3"	1-1/4"	Thermoplastic Rubber	Precision Ball	190 lbs	4-5/16"	2-29/32"	CH-03TPP-125-SW-____
	1-1/4"	Polyurethane TPU	Precision Ball	190 lbs	4-5/16"	2-29/32"	CH-03PYP-125-SW-____
4"	1-1/4"	Thermoplastic Rubber	Precision Ball	240 lbs	5-5/16"	3-37/64"	CH-04TPP-125-SW-____
	1-1/4"	Polyurethane TPU	Precision Ball	240 lbs	5-5/16"	3-37/64"	CH-04PYP-125-SW-____
5"	1-1/4"	Thermoplastic Rubber	Precision Ball	260 lbs	6-5/16"	4-7/32"	CH-05TPP-125-SW-____
	1-1/4"	Polyurethane TPU	Precision Ball	260 lbs	6-5/16"	4-7/32"	CH-05PYP-125-SW-____
6"	1-1/4"	Thermoplastic Rubber	Precision Ball	260 lbs	7-9/32"	4-39/64"	CH-06TPP-125-SW-____
	1-1/4"	Polyurethane TPU	Precision Ball	260 lbs	7-9/32"	4-39/64"	CH-06PYP-125-SW-____



*Swivel radius for total lock and direction lock models increases to: 3"=4-1/4, 4"=4-35/64, 5" & 6"=4-55/64.

Chrome Hospital Swivel Top Plate

Call Toll Free **1-800-215-8220** to Order Casters or for More Information.




Total Lock
Change "SW"
to "TL". **Red**
sticker on pedal.

Direction Lock
Change "SW"
to "DL". **Green**
sticker on pedal.

Swivel Top Plate Models

Wheel Diameter	Tread Width	Tread Material	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius	Swivel Part Number
3"	1-1/4"	Thermoplastic Rubber	Precision Ball	190 lbs	4-7/16"	2-29/32"	CH-03TPP-125-SW-TP01
	1-1/4"	Polyurethane TPU	Precision Ball	190 lbs	4-7/16"	2-29/32"	CH-03PYP-125-SW-TP0
4"	1-1/4"	Thermoplastic Rubber	Precision Ball	240 lbs	5-7/16"	3-37/64"	CH-04TPP-125-SW-TP01
	1-1/4"	Polyurethane TPU	Precision Ball	240 lbs	5-7/16"	3-37/64"	CH-04PYP-125-SW-TP01
5"	1-1/4"	Thermoplastic Rubber	Precision Ball	220	6-7/16"	4-7/32"	CH-05TPP-125-SW-TP01
	1-1/4"	Polyurethane TPU	Precision Ball	220	6-7/16"	4-7/32"	CH-05PYP-125-SW-TP01
6"	1-1/4"	Thermoplastic Rubber	Precision Ball	240	7-13/32"	4-39/64"	CH-06TPP-125-SW-TP01
	1-1/4"	Polyurethane TPU	Precision Ball	240	7-13/32"	4-39/64"	CH-06PYP-125-SW-TP01



*Swivel radius for total lock and direction lock models increases to: 3"=4-1/4, 4"=4-35/64, 5" & 6"=4-55/64.

Rigid Top Plate Models

Wheel Diameter	Tread Width	Tread Material	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius	Swivel Part Number
3"	1-1/4"	Thermoplastic Rubber	Precision Ball	190 lbs	4-7/16"	N/A	CH-03TPP-125-RG-TP01
	1-1/4"	Polyurethane TPU	Precision Ball	190 lbs	4-7/16"	N/A	CH-03PYP-125-RG-TP0
4"	1-1/4"	Thermoplastic Rubber	Precision Ball	240 lbs	5-7/16"	N/A	CH-04TPP-125-RG-TP01
	1-1/4"	Polyurethane TPU	Precision Ball	240 lbs	5-7/16"	N/A	CH-04PYP-125-RG-TP01
5"	1-1/4"	Thermoplastic Rubber	Precision Ball	220	6-7/16"	N/A	CH-05TPP-125-RG-TP01
	1-1/4"	Polyurethane TPU	Precision Ball	220	6-7/16"	N/A	CH-05PYP-125-RG-TP01
6"	1-1/4"	Thermoplastic Rubber	Precision Ball	240	7-13/32"	N/A	CH-06TPP-125-RG-TP01
	1-1/4"	Polyurethane TPU	Precision Ball	240	7-13/32"	N/A	CH-06PYP-125-RG-TP01

