

MRI Conditional Casters



Call **Service Caster** Toll Free **1-800-215-8220** to Order Casters and for Additional Information.



Features	Applications	Options
----------	--------------	---------

- | | | |
|---|---|--|
| <ul style="list-style-type: none"> • Rated MRI Conditional for use in MRI examination rooms • 100% corrosion resistant components • RoHS Compliant • Soft 70-75/A durometer tread constructed of high-tech thermoplastic elastomer • High load ratings • Quiet mobility | <ul style="list-style-type: none"> • Medical Equipment • Hospital Carts • Electronic Equipment | <p>Fasteners: Additional fastener options available upon request (minimums may apply).</p> <p>Brake: To order insert [-B] at the end of the Part Number.</p> |
|---|---|--|



Grip Ring Stem Models

Wheel Diameter	Tread Material	Dynamic Load	Mounting Height	Swivel Radius	Part Number	Fastening Selection
50mm	Thermoplastic Elastomer	75 lbs.	2-1/4"	1-13/16"	PSF50__GR-MR	273, 202
60mm	Thermoplastic Elastomer	100 lbs.	2-1/2"	2-5/8"	PSF60__GR-MR	273, 202
75mm	Thermoplastic Elastomer	165 lbs.	3-3/16"	2-1/2"	PSF75__GR-MR	273, 202

For brake add [-B] to end of part number. Swivel radius for 50mm is 2-3/8", 60mm is 2-1/2", 75mm is 3-3/16", 100mm is 4-1/2", 125mm is 5-1/8".



To order include fastener code. Example: (PSF50**273**GR-MR).



Threaded Stem Models

Wheel Diameter	Tread Material	Dynamic Load	Mounting Height	Swivel Radius	Part Number	Fastening Selection
50mm	Thermoplastic Elastomer	75 lbs.	2-1/4"	1-13/16"	PSF50651GR-MR	651
60mm	Thermoplastic Elastomer	100 lbs.	2-1/2"	2-5/8"	PSF60651GR-MR	651
75mm	Thermoplastic Elastomer	165 lbs.	3-3/16"	2-1/2"	PSF75651GR-MR	651

For brake add [-B] to end of part number. Swivel radius for 50mm is 2-3/8", 60mm is 2-1/2", 75mm is 3-3/16", 100mm is 4-1/2", 125mm is 5-1/8".

