

Stainless Hospital Call Toll Free 1-800-215-8220 to Order Casters or for More Information.



Features

- 304 Stainless Steel, Polished
- Dual Ball Swivel Raceways for added strength
- Total Lock Brake models lock both swivel and wheel
- Directional lock models lock swivel only (helps with Steering)
- Precision ball bearings in wheels for easier rollability
- Wheels have full plastic thread guards for added protection

Applications

- Food Service
- Case Carts
- Medical Equipment
- Institutional Equipment
- Laboratory Equipment
- Animal Cages
- Pharmaceutical Equipment


Hollow Kingpin Models

Wheel Diameter	Tread Width	Tread Material	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius*	Swivel Part Number
3"	1-1/4"	Thermoplastic Rubber	Precision Ball	165 lbs	4-5/16"	3-37/64"	SS-03TPP-125-SW-HK01
	1-1/4"	Anti-Microbial TPR	Precision Ball	165 lbs	4-5/16"	3-37/64"	SS-03AMP-125-SW-HK01
	1-1/4"	Polyurethane TPU	Precision Ball	165 lbs	4-5/16"	3-37/64"	SS-03PYP-125-SW-HK01
4"	1-1/4"	Thermoplastic Rubber	Precision Ball	190 lbs	5-5/16"	3-37/64"	SS-04TPP-125-SW-HK01
	1-1/4"	Anti-Microbial TPR	Precision Ball	190 lbs	5-5/16"	3-37/64"	SS-04AMP-125-SW-HK01
	1-1/4"	Polyurethane TPU	Precision Ball	190 lbs	5-5/16"	3-37/64"	SS-04PYP-125-SW-HK01
5"	1-1/4"	Thermoplastic Rubber	Precision Ball	220 lbs	6-5/16"	4-7/32"	SS-05TPP-125-SW-HK01
	1-1/4"	Anti-Microbial TPR	Precision Ball	220 lbs	6-5/16"	4-7/32"	SS-05AMP-125-SW-HK01
	1-1/4"	Polyurethane TPU	Precision Ball	220 lbs	6-5/16"	4-7/32"	SS-05PYP-125-SW-HK01
6"	1-1/4"	Thermoplastic Rubber	Precision Ball	240 lbs	7-9/32"	4-39/64"	SS-06TPP-125-SW-HK01
	1-1/4"	Anti-Microbial TPR	Precision Ball	240 lbs	7-9/32"	4-39/64"	SS-06AMP-125-SW-HK01
	1-1/4"	Polyurethane TPU	Precision Ball	240 lbs	7-9/32"	4-39/64"	SS-06PYP-125-SW-HK01



Total Lock
Change "SW"
to "TL". Red
sticker on pedal.

Direction Lock
Change "SW"
to "DL". Green
sticker on pedal.

HK01 
Caster is provided
assembled. Change
HK01 code to HKU1
for unassembled.
1/2" I.D.

Anti-Microbial wheels have light green tread.

*Swivel radius for total lock and directional lock models increases to: 3"=4-1/4,

4"=4-35/64, 5" & 6"=4-55/64.

Stainless Hospital

Call Toll Free **1-800-215-8220** to Order Casters or for More Information.




Total Lock
Change "SW"
to "TL". **Red**
sticker on pedal.

Direction Lock
Change "SW"
to "DL". **Green**
sticker on pedal.

Threaded Stem Models

Wheel Diameter	Tread Width	Tread Material	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius*	Swivel Part Number
3"	1-1/4"	Thermoplastic Rubber	Precision Ball	165 lbs	5-5/16"	3-37/64"	SS-03TPP-125-SW-____
	1-1/4"	Anti-Microbial TPR	Precision Ball	165 lbs	5-5/16"	3-37/64"	SS-03AMP-125-SW-____
	1-1/4"	Polyurethane TPU	Precision Ball	165 lbs	5-5/16"	3-37/64"	SS-03PYP-125-SW-____
4"	1-1/4"	Thermoplastic Rubber	Precision Ball	190 lbs	5-5/16"	3-37/64"	SS-04TPP-125-SW-____
	1-1/4"	Anti-Microbial TPR	Precision Ball	190 lbs	5-5/16"	3-37/64"	SS-04AMP-125-SW-____
	1-1/4"	Polyurethane TPU	Precision Ball	190 lbs	5-5/16"	3-37/64"	SS-04PYP-125-SW-____
5"	1-1/4"	Thermoplastic Rubber	Precision Ball	220 lbs	6-5/16"	4-7/32"	SS-05TPP-125-SW-____
	1-1/4"	Anti-Microbial TPR	Precision Ball	220 lbs	6-5/16"	4-7/32"	SS-05AMP-125-SW-____
	1-1/4"	Polyurethane TPU	Precision Ball	220 lbs	6-5/16"	4-7/32"	SS-05PYP-125-SW-____
6"	1-1/4"	Thermoplastic Rubber	Precision Ball	240 lbs	7-9/32"	4-39/64"	SS-06TPP-125-SW-____
	1-1/4"	Anti-Microbial TPR	Precision Ball	240 lbs	7-9/32"	4-39/64"	SS-06AMP-125-SW-____
	1-1/4"	Polyurethane TPU	Precision Ball	240 lbs	7-9/32"	4-39/64"	SS-06PYP-125-SW-____



Anti-Microbial wheels have light green tread.

*Swivel radius for total lock and direction lock models increases to: 3"=4-1/4, 4"=4-35/64, 5" & 6"=4-55/64.




Total Lock
Change "SW"
to "TL". **Red**
sticker on pedal.

Direction Lock
Change "SW"
to "DL". **Green**
sticker on pedal.

Swivel Top Plate Models

Wheel Diameter	Tread Width	Tread Material	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius	Swivel Part Number
3"	1-1/4"	Thermoplastic Rubber	Precision Ball	165 lbs	5-7/16"	3-37/64"	SS-03TPP-125-SW-TP01
	1-1/4"	Anti-Microbial TPR	Precision Ball	165 lbs	5-7/16"	3-37/64"	SS-03AMP-125-SW-TP01
	1-1/4"	Polyurethane TPU	Precision Ball	165 lbs	5-7/16"	3-37/64"	SS-03PYP-125-SW-TP01
4"	1-1/4"	Thermoplastic Rubber	Precision Ball	190 lbs	5-7/16"	3-37/64"	SS-04TPP-125-SW-TP01
	1-1/4"	Anti-Microbial TPR	Precision Ball	190 lbs	5-7/16"	3-37/64"	SS-04AMP-125-SW-TP01
	1-1/4"	Polyurethane TPU	Precision Ball	190 lbs	5-7/16"	3-37/64"	SS-04PYP-125-SW-TP01
5"	1-1/4"	Thermoplastic Rubber	Precision Ball	220 lbs	6-7/16"	4-7/32"	SS-05TPP-125-SW-TP01
	1-1/4"	Anti-Microbial TPR	Precision Ball	220 lbs	6-7/16"	4-7/32"	SS-05AMP-125-SW-TP01
	1-1/4"	Polyurethane TPU	Precision Ball	220 lbs	6-7/16"	4-7/32"	SS-05PYP-125-SW-TP01
6"	1-1/4"	Thermoplastic Rubber	Precision Ball	240 lbs	7-13/32"	4-39/64"	SS-06TPP-125-SW-TP01
	1-1/4"	Anti-Microbial TPR	Precision Ball	240 lbs	7-13/32"	4-39/64"	SS-06AMP-125-SW-TP01
	1-1/4"	Polyurethane TPU	Precision Ball	240 lbs	7-13/32"	4-39/64"	SS-06PYP-125-SW-TP01



Anti-Microbial wheels have light green tread.

*Swivel radius for total lock and direction lock models increases to: 3"=4-1/4, 4"=4-35/64, 5" & 6"=4-55/64.