

Bassick Business Machine 00 Series


1-800-215-8220



Side Lock Brake
Swivel radius is 2-5/16".
Add [B] at end of model.

Grip Ring Stem (Brass Band) Models

Wheel Dia.	Tread Width	Tread Type (# Wheels)	Dynamic Load	Mounting Height	Swivel Radius	Part Number	Fastening Selection
2"	1-13/16"	Soft Rubber (2)	180	2-3/4"	2"	C0020273ZN-SFR01(GG)	273
	1-13/16"	TPR (2)	180	2-3/4"	2"	C0020273ZN-TPR01(GG)	273
	1-13/16"	Hard Rubber (2)	225	2-3/4"	2"	C0020273ZN-HDR01(GG)	273
	1-13/16"	Polyolefin (2)	225	2-3/4"	2"	C0020273ZN-POS01(KK)	273
	1-13/16"	Polyolefin Log (1)	300	2-3/4"	2"	C0020273ZN-POL01(KK)	273



Side Lock Brake
Swivel radius is 2-5/16".
Add [B] at end of model.

Swivel Top Plate Models

Wheel Dia.	Tread Width	Tread Type (# Wheels)	Dynamic Load	Mounting Height	Swivel Radius	Part Number	Fastening Selection
2"	1-13/16"	Soft Rubber (2)	180	2-13/16"	2"	C0020120ZN-SFR01(GG)	120
	1-13/16"	TPR (2)	180	2-13/16"	2"	C0020120ZN-TPR01(GG)	120
	1-13/16"	Hard Rubber (2)	225	2-13/16"	2"	C0020120ZN-HDR01(GG)	120
	1-13/16"	Polyolefin (2)	225	2-13/16"	2"	C0020120ZN-POS01(KK)	120
	1-13/16"	Polyolefin Log (1)	300	2-13/16"	2"	C0020120ZN-POL01(KK)	120

