



Bassick Business Machine 00 Series



Features

- Dual ball bearing raceway construction
- High load capacity
- Sleek, low profile design

Applications

- Electronic Equipment
- Business Machines
- Store Fixtures
- Laboratory Equipment

Options

Side Lock Brake: To order, add [B] to end of model.

Wheel Selection



Threaded Stem Models

Wheel Dia.	Tread Width	Tread Type (# Wheels)	Dynamic Load	Mounting Height	Swivel Radius	Part Number	Fastening Selection
2"	1-13/16"	Soft Rubber (2)	180	2-3/4"	2"	C0020_ZN-SFR01(GG)	741, 748
	1-13/16"	TPR (2)	180	2-3/4"	2"	C0020_ZN-TPR01(GG)	741, 748
	1-13/16"	Hard Rubber (2)	225	2-3/4"	2"	C0020_ZN-HDR01(GG)	741, 748
	1-13/16"	Polyolefin (2)	225	2-3/4"	2"	C0020_ZN-POS01(KK)	741, 748
	1-13/16"	Polyolefin Log (1)	300	2-3/4"	2"	C0020_ZN-POL01(KK)	741, 748

741

748



To order include fastener code.
Example: C0020741ZN-SFR01(KK)

Side Lock Brake
Swivel radius is 2-5/16".
Add [B] at end of model.

