



Bassick XX/YY



Features

- Low overall height combined with heavy load requirements
- Double ball bearing raceways
- Heavy, staked kingpin
- Yellow dichromate finish for added corrosion resistance

Applications

- Electronic Equipment
- Material Handling

Wheel Selection



Hard or Soft Rubber



Phenolic



Steel or Sintered Iron



XX Swivel Top Plate Models

Wheel Dia.	Tread Width	Tread Type	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius	Part Number
3"	1-5/16"	Soft Rubber	Roller	160	4-5/16"	2-7/8"	CXX30155YZ-SFR51(KK)
	1-5/16"	Hard Rubber	Roller	225	4-5/16"	2-7/8"	CXX30155YZ-HDR51(KK)
	1-5/16"	Phenolic	Roller	400	4-5/16"	2-7/8"	CXX30155YZ-PHN51(KK)
	1-5/16"	Sintered Iron	Roller	900	4-5/16"	2-7/8"	CXX30155YZ-STMS1(GG)
4"	1-5/8"	Soft Rubber	Roller	200	5-9/32"	3-3/8"	CXX40155YZ-SFR51(KK)
	1-5/8"	Hard Rubber	Roller	300	5-9/32"	3-3/8"	CXX40155YZ-HDR51(KK)
	1-5/8"	Phenolic	Roller	600	5-9/32"	3-3/8"	CXX40155YZ-PHN51(KK)
	1-5/8"	Steel	Roller	900	5-9/32"	3-3/8"	CXX40155YZ-STL51(GG)



YY Rigid Top Plate Models

Wheel Dia.	Tread Width	Tread Type	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius	Part Number
3"	1-5/16"	Soft Rubber	Roller	160	4-5/16"	N/A	CYY30155YZ-SFR51(KK)
	1-5/16"	Hard Rubber	Roller	225	4-5/16"	N/A	CYY30155YZ-HDR51(KK)
	1-5/16"	Phenolic	Roller	400	4-5/16"	N/A	CYY30155YZ-PHN51(KK)
	1-5/16"	Sintered Iron	Roller	900	4-5/16"	N/A	CYY30155YZ-STMS1(GG)
4"	1-5/8"	Soft Rubber	Roller	200	5-9/32"	N/A	CYY40155YZ-SFR51(KK)
	1-5/8"	Hard Rubber	Roller	300	5-9/32"	N/A	CYY40155YZ-HDR51(KK)
	1-5/8"	Phenolic	Roller	600	5-9/32"	N/A	CYY40155YZ-PHN51(KK)
	1-5/8"	Steel	Roller	900	5-9/32"	N/A	CYY40155YZ-STL51(GG)

