

Wheels

Mono Tech



MonoTech wheels are constructed of a special mix of monprene that rejects almost every type of floor debris and has a high load capacity. Their soft durometer allows for maximum shock absorption and cushions the ride to protect your equipment, cargo and floors while reducing noise. They are resistant to most chemicals and oils. The rounded tread offers better mobility and is chemically bonded to the core.

Wheel Diameter	Tread Width	Bearing	Thread Guard	Hub Length	Axle Size	Color Tread/Core	Dynamic Load	Durometer/Shore Scale	Part Number
3"	15/16"	Plain Bore	None	1.01"	1/4"	g rey/g rey	120 lbs.	65A	009001
3-1/2"	1-1/4"	Plain Bore	None	1.57"	3/8"	g rey/g rey	250 lbs	65A	008987
	1-1/4"	Ball Bearing	None	1.57"	3/8"	g rey/g rey	250 lbs	65A	008990
4"	1"	Plain Bore	None	1.18"	5/16"	g rey/g rey	150 lbs	65A	009003
	1-1/4"	Plain Bore	None	1.57"	3/8"	g rey/g rey	300 lbs	65A	008988
	1-1/4"	Ball Bearing	Full	1.57"	3/8"	g rey/g rey	300 lbs	65A	008991
5"	1"	Plain Bore	None	1.18"	5/16"	g rey/g rey	160 lbs	65A	007315
	1"	Precision	Full	1.18"	5/16"	g rey/g rey	160 lbs	65A	007320
	1-1/4"	Plain Bore	None	1.57"	3/8"	g rey/g rey	325 lbs	65A	008989
	1-1/4"	Ball Bearing	Full	1.57"	3/8"	g rey/g rey	325 lbs	65A	008992