

Wheels

Thermoplastic Rubber (TPR)



Thermoplastic Rubber (TPR) wheels offer resistance to oils and chemicals and are a great alternative to standard rubber wheels. The tread is mechanically bonded to the core to eliminate separation.

Wheel Diameter	Tread Width	Bearing	Thread Guard	Hub Length	Axle Size	Color Tread/Core	Dynamic Load	Durometer/Shore Scale	Part Number
2"	13/16"	Plain Bore	None	0.90"	1/4"	grey/black	80 lbs	40D	007962
	13/16"	Plain Bore	None	0.92"	5/16"	grey/grey	80 lbs	40D	618713
2-1/2"	13/16"	Plain Bore	None	0.90"	1/4"	grey/black	90 lbs.	40D	007964
3"	13/16"	Plain Bore	None	1.00"	1/4"	grey/black	125 lbs	40D	007967
	1-1/4"	Delrin	None	1.5"	3/8"	grey/grey	210 lbs	85A	009014
	1-1/4"	Ball Bearing	None	1.625"	3/8"	grey/grey	210 lbs	85A	009104
	1-1/4"	Precision	Full	1.625"	3/8"	grey/grey	210 lbs	85A	009163
3-1/2"	1-1/4"	Delrin	None	1.5"	3/8"	grey/grey	250 lbs	85A	009197
	1-1/4"	Ball Bearing	Partial	1.625"	3/8"	grey/grey	250 lbs	85A	009198
4"	15/16"	Plain Bore	None	1.15"	5/16"	grey/black	125 lbs	75A	007273
	1-1/4"	Delrin	None	1.5"	3/8"	grey/grey	260 lbs	85A	009018
	1-1/4"	Ball Bearing	Partial	1.625"	3/8"	grey/grey	260 lbs	85A	009108
	1-1/4"	Precision	Full	1.625"	3/8"	grey/grey	260 lbs	85A	009167
5"	1"	Plain Bore	None	1.15"	5/16"	grey/black	150 lbs	75A	007313
	1-1/4"	Delrin	None	1.5"	3/8"	grey/grey	280 lbs	85A	009022
	1-1/4"	Ball Bearing	Partial	1.625"	3/8"	grey/grey	280 lbs	85A	009112
	1-1/4"	Precision	Full	1.625"	3/8"	grey/grey	280 lbs	85A	009171