

Bassick

INSTITUTIONAL CASTERS • SERIES 70 SWIVEL • 2", 2½ and 3" DIAMETER WHEELS FOR FURNITURE AND EQUIPMENT WEIGHING UP TO 380 POUNDS.

These casters provide excellent performance on light wood or metal institutional equipment requiring easy movement within small areas. Typical uses are book racks, bed side cabinets and typewriter stands.

SWIVEL: Double level, hardened, full ball bearing swivel for easy swiveling and long life.

FINISH: Heavy zinc plate for rust prevention and bright appearance.

WHEEL BRAKE: Step on wheel brake supplied where indicated with prefix SB.

1 1/16" x 1 3/16" bolt hole spacing
3/16" mounting bolt diameter
1 3/16" x 2" top plate

WHEEL			SWIVEL CASTER					
Dia. In.	Tread Width In.	Bearing Type	Load Cap. Lbs.	Caster Height In.	Swivel Radius In.	Approx. Weight Lbs.	Bassick No.	Stand. EDP No.

BACO Wheel. Non-marking, non-staining soft rubber tread molded to hard rubber core for floor protection and quiet operation. Recommended for use on hard floors.

2	7/8	Self Lube	75	2 3/8	1 7/8	1/3	9706RP	10053
2	7/8	Self Lube	75	2 5/8	2 1/4	1/2	SB9706RP	10054
2 1/2	1 3/16	Self Lube	90	3 1/16	2 1/4	1/2	10706RP	10103
2 1/2	1 3/16	Self Lube	90	3 1/16	2 3/8	2/3	SB10706RP	10104
3	1 3/16	Self Lube	95	3 5/8	2 5/8	2/3	L13706RP	10178
3	1 3/16	Self Lube	95	3 5/8	2 7/8	2/3	SBL13706RP	10180

SB Prefix, Wheel Brake Caster



Step-on wheel brakes are available as indicated in the tables by the prefix *SB.

INSTITUTIONAL CASTERS • SERIES 70 SWIVEL • SERIES 71 RIGID • 3", 4" and 5" DIAMETER WHEELS • FOR FURNITURE AND EQUIPMENT WEIGHING UP TO 600 POUNDS.

1 3/4" x 2 7/8" — 3 bolt hole spacing
3/16" mounting bolt diameter
2 3/4" x 3 3/4" top plate

These casters with larger wheels and larger swivel bearing are for heavier service and greater movement. School audio-visual stands, room service carts, display stands and cabinets and utility tables are typical uses.



13716 RP

SWIVEL: Double level, hardened, full ball bearing swivel for easy swiveling and long life.

FINISH: Heavy zinc plate for rust prevention and bright appearance.

WHEEL BRAKE: Step on wheel brake supplied where indicated with prefix SB.

H13706 RP

WHEEL			Load Cap. Lbs.	Caster Height In.	SWIVEL CASTER				RIGID CASTER		
Dia. In.	Tread Width In.	Bearing Type			Swivel Radius In.	Approx. Weight Lbs.	Bassick No.	Stand. EDP No.	Approx. Weight Lbs.	Bassick No.	Stand. EDP No.

BACO Wheel. Non-Marking, non-staining soft rubber tread molded to hard rubber core for floor protection and quiet operation. Recommended for use on hard floors.

3	1 3/16	Self Lube	100	3 3/4	2 3/4	1	H13706RP	10181	1	13716RP	10185
3	1 3/16	Self Lube	100	3 3/4	3	1	SBH13706RP	10183	—	—	—
4	7/8	Self Lube	110	4 3/4	3 5/8	1 1/2	14706RP	10293	1 1/2	14716RP	10297
4	7/8	Self Lube	110	4 3/4	3 3/8	1 1/2	SB14706RP	10295	—	—	—
5	1 5/16	Self Lube	125	5 3/4	4	2	15706RP	10421	1 3/4	15716RP	10425
5	1 5/16	Self Lube	125	5 3/4	4	2	SB15706RP	10423	—	—	—

ATLASITE Wheel. Non-marking molded hard rubber for greater load capacity and easier rolling. Recommended for use on carpet.

3	1 3/16	Self Lube	125	3 3/4	2 3/4	1	H13709ERP	11903	1	13719ERP	11904
3	1 3/16	Self Lube	125	3 3/4	3	1	SBH13709ERP	11905	—	—	—
4	7/8	Self Lube	135	4 3/4	3 5/8	1 1/2	14709GRP	11906	1 1/2	14719GRP	11907
4	7/8	Self Lube	135	4 3/4	3 3/8	1 1/2	SB14709GRP	11908	—	—	—
5	1 5/16	Self Lube	150	5 3/4	4	2	15709RP	10422	1 3/4	15719RP	10427
5	1 5/16	Self Lube	150	5 3/4	4	2	SB15709RP	10424	—	—	—

SB Prefix, Wheel Brake Caster