

***Bassick* HONCHO 900**

Material Handling Casters

For platform trucks, warehouse trucks, mobile containers and other material handling trucks carrying up to 3,600 pounds in hand pushed or conveyor towed applications.

SERIES AS SWIVEL, SERIES AR RIGID 5", 6" & 8" Diameter Wheels

Heat treat hardened bearing races and balls for easier swiveling and long life.

Polymer seal retains lubricant and excludes contaminants for longer life, better swiveling.

Machine welding for consistent quality, strength and neat appearance.

Easily accessible but protected Alemite lubrication fitting for swivel bearing.

Husky king pin, thick steel bearing races for added strength.

Zinc chromate finish for corrosion resistance over double that of ordinary zinc plate.

Polymer plastic wheel bearing seals retain lubricant, exclude contaminants and reduce friction and wear between wheel hub and caster legs.

Easily accessible but protected Alemite lubrication fitting for wheel roller bearings.



6AS3R-7

All new welded construction with strength to withstand conveyor use and the continuous impacts of transport in over highway trucks. Supplied standard with sealed swivel bearing to retain lubricant and exclude contaminants. Easy to clean and keep clean, these casters have found good application in food processing industries.



Bolt hole spacing $2\frac{5}{8}'' \times 3\frac{5}{8}''$
 slotted to $3'' \times 3''$
 Mounting bolt dia. $\frac{3}{8}''$
 Top plate size $4'' \times 4\frac{1}{2}''$

WHEEL			Load Cap. Lbs.	Caster Height In.	SWIVEL CASTER				RIGID CASTER		
Dia. In.	Tread Width In.	Bearing Type			Swivel Radius In.	Approx. Weight Lbs.	Bassick No.	Stand. EDP No.	Approx. Weight Lbs.	Bassick No.	Stand. EDP No.

BACO WHEEL. Soft rubber tread molded to hard rubber core provides floor and load protection and quiet operation. Recommended for hand pushed equipment on hard floors.

5	2	Roller	425	6 $\frac{1}{2}$	3 $\frac{15}{16}$	5 $\frac{1}{2}$	5AS6-2	11764	4 $\frac{1}{2}$	5AR6-2	11765
6	2	Roller	475	7 $\frac{1}{2}$	4 $\frac{5}{8}$	7	6AS6-2	11768	5 $\frac{1}{2}$	6AR6-2	11769

ALCORE/RUBBER TREAD WHEEL. Soft rubber tread bonded to aluminum core provides maximum floor and load protection, impact strength and quiet operation. Recommended for hand pushed or conveyor towed operation on hard floors. Supplied standard with sealed roller wheel bearing.

5	2	Seal Roller	450	6 $\frac{1}{2}$	3 $\frac{15}{16}$	5 $\frac{1}{2}$	5AS3R-7	12348	4 $\frac{1}{2}$	5AR3R-7	12351
6	2	Seal Roller	500	7 $\frac{1}{2}$	4 $\frac{5}{8}$	7	6AS3R-7	12349	5 $\frac{1}{2}$	6AR3R-7	12352
8	2	Seal Roller	600	9 $\frac{1}{2}$	6	9	8AS3R-7	12350	7 $\frac{1}{2}$	8AR3R-7	12353

BRAVOTHANE WHEEL. Tough, resilient polyurethane tread interlocked to polypropylene core. Provides quiet service with floor protection for hand pushed applications. Excellent resistance to corrosion. Use on hard floors and carpet.

5	2	Seal Lube	700	6 $\frac{1}{2}$	3 $\frac{15}{16}$	5 $\frac{1}{2}$	5AS8PT	15051	4 $\frac{1}{2}$	5AR8PT	15052
5	2	Seal Roller	700	6 $\frac{1}{2}$	3 $\frac{15}{16}$	5 $\frac{1}{2}$	5AS8P-7	15043	4 $\frac{1}{2}$	5AR8P-7	15044
6	2	Seal Lube	750	7 $\frac{1}{2}$	4 $\frac{5}{8}$	6 $\frac{1}{2}$	6AS8PT	15053	5	6AR8PT	15054
6	2	Seal Roller	750	7 $\frac{1}{2}$	4 $\frac{5}{8}$	6 $\frac{1}{2}$	6AS8P-7	15046	5	6AR8P-7	15047
8	2	Seal Lube	750	9 $\frac{1}{2}$	6	8 $\frac{1}{2}$	8AS8PT	15055	7	8AR8PT	15056
8	2	Seal Roller	750	9 $\frac{1}{2}$	6	8 $\frac{1}{2}$	8AS8P-7	15049	7	8AR8P-7	15050

BRAVO WHEEL. High impact polypropylene material for high load capacity and floor protection. Impervious to water, acid and most chemicals. Recommended for hand pushed equipment on hard floors and carpets. Roller bearing wheels for easy rolling. Plain bearing wheels for economy, and for use in corrosive conditions.

5	2	Plain	650	6 $\frac{1}{2}$	3 $\frac{15}{16}$	4 $\frac{3}{4}$	5AS8M	12032	4 $\frac{1}{4}$	5AR8M	12033
5	2	Seal Roller	650	6 $\frac{1}{2}$	3 $\frac{15}{16}$	5	5AS8M-7	12034	4 $\frac{1}{2}$	5AR8M-7	12035
6	2	Plain	700	7 $\frac{1}{2}$	4 $\frac{5}{8}$	5 $\frac{3}{4}$	6AS8M	12036	4 $\frac{3}{4}$	6AR8M	12037
6	2	Seal Roller	700	7 $\frac{1}{2}$	4 $\frac{5}{8}$	6	6AS8M-7	12038	5	6AR8M-7	12039
8	2	Seal Roller	900	9 $\frac{1}{2}$	6	8	8AS8M-7	12042	6	8AR8M-7	12043

ATLASITE WHEEL. Water resistant, non marking molded hard rubber wheel combines high capacity and easy rolling with floor protection. Recommended for hand pushed equipment on hard floors and carpet.

5	2	Roller	600	6 $\frac{1}{2}$	3 $\frac{15}{16}$	5 $\frac{1}{2}$	5AS9-2	11774	4 $\frac{1}{2}$	5AR9-2	11775
6	2	Roller	650	7 $\frac{1}{2}$	4 $\frac{5}{8}$	7	6AS9-2	11778	6	6AR9-2	11779

HONCHO/POLYURETHANE Tread Wheel. Tough, resilient polyurethane mechanically interlocked to husky die cast aluminum core for extra abuse conditions.

5	2	Seal Roller	900	6 $\frac{1}{2}$	3 $\frac{15}{16}$	5 $\frac{1}{2}$	5AS3P-7	12801	4 $\frac{1}{2}$	5AR3P-7	12800
6	2	Seal Roller	900	7 $\frac{1}{2}$	4 $\frac{5}{8}$	6 $\frac{1}{2}$	6AS3P-7	12811	5	6AR3P-7	12810
8	2	Seal Roller	900	9 $\frac{1}{2}$	6	8 $\frac{1}{2}$	8AS3P-7	12821	7	8AR3P-7	12820

CANAPHIN WHEEL. Phenolic resin plastic reinforced with new low water absorption macerated canvas. High load capacity, impact strength, floor protection and easy, quiet rolling. Resistant to many chemicals, acids, solvents, water solutions. Operating temperatures from -40°F to $+300^{\circ}\text{F}$. Clean, non-marking wheel for use on hand pushed and power moved equipment on hard, smooth floors or carpet. Supplied standard with roller bearing in wheel.

5	2	Seal Roller	900	6 $\frac{1}{2}$	3 $\frac{15}{16}$	5	5AS8-7	11782	4 $\frac{1}{2}$	5AR8-7	11783
6	2	Seal Roller	900	7 $\frac{1}{2}$	4 $\frac{5}{8}$	6	6AS8-7	11784	5	6AR8-7	11785
8	2	Seal Roller	900	9 $\frac{1}{2}$	6	8	8AS8-7	11786	6 $\frac{1}{2}$	8AR8-7	11787

SEMI-STEEL WHEEL. Cast iron enriched with steel for high load capacity, easy rolling and resistance to rough and chip littered floors. Smooth, machined treads reduce floor damage and noise.

5	2	Roller	900	6 $\frac{1}{2}$	3 $\frac{15}{16}$	8	5AS1-2	11754	7	5AR1-2	11755
6	2	Roller	900	7 $\frac{1}{2}$	4 $\frac{5}{8}$	9	6AS1-2	11758	8	6AR1-2	11759
8	2	Roller	900	9 $\frac{1}{2}$	6	12	8AS1-2	11760	11	8AR1-2	11761

Bassick HONCHO 900 CASTERS WITH COMBINATION SWIVEL LOCKS AND WHEEL BRAKES.

Castered equipment weighing up to 3600 lbs. held firmly in place by easily applied brakes.

SERIES B AS, 5" 6" & 8" DIA. WHEELS.

Foot operated pedal simultaneously locks wheel from rolling and swivel from turning. Castered equipment held firmly in place. Easy upward pressure on pedal releases brakes on both swivel and wheel to restore full mobility

Swivel: Supplied Standard with sealed swivel bearings to retain lubricant and exclude contaminants. Heat treat hardened bearing races for easier swiveling and long life.

Finish: Zinc Chromate for superior corrosion resistance.



B6AS3R-7

Bolt hole spacing 2⁵/₈" x 3⁵/₈"
 slotted to 3" x 3"
 Mounting bolt dia. 3/8"
 Top plate size 4" x 4¹/₂"

WHEEL			Load Cap. Lbs.	Caster Height In.	SWIVEL CASTER			
Dia. In.	Tread Width In.	Bearing Type			Swivel Radius In.	Approx. Weight Lbs.	Bassick No.	Stand EDP No.

BACO/SOFT RUBBER TREAD WHEEL Soft rubber tread molded to hard rubber core provides floor and load protection and quiet operation. Recommended for hand pushed equipment on hard floors.

5	2	Roller	425	6-1/2	3-15/16	6-1/2	B5AS6-2	12253
6	2	Roller	475	7-1/2	4-5/8	8	B6AS6-2	12254

ALCORE/RUBBER TREAD WHEEL. Soft rubber tread bonded to aluminum core provides maximum floor and load protection, impact strength and quiet operation. Recommended for hand pushed or conveyor towed operation on hard floors. Supplied standard with sealed roller wheel bearing.

5	2	Seal Roller	450	6-1/2	3-15/16	6-1/2	B5AS3R-7	12339
6	2	Seal Roller	500	7-1/2	4-5/8	8	B6AS3R-7	12340
8	2	Seal Roller	600	9-1/2	6	11	B8AS3R-7	12341

BRAVOTHANE Wheel. Tough, resilient polyurethane tread interlocked to polypropylene core. Provides quiet service with floor protection for hand pushed applications. Excellent resistance to corrosion. Use on hard floors and carpet.

5	2	Seal Roller	700	6-1/2	3-15/16	5	B5AS8P-7	15042
6	2	Seal Roller	750	7-1/2	4-5/8	6	B6AS8P-7	15045
8	2	Seal Roller	750	9-1/2	6	8	B8AS8P-7	15048

BRAVO WHEEL. High impact polypropylene material for high load capacity and floor protection. Impervious to water, acid and most chemicals. Recommended for hand pushed equipment on hard floors and carpets. Roller bearing wheels for easy rolling.

5	2	Seal Roller	650	6-1/2	3-15/16	5	B5AS8M-7	12259
6	2	Seal Roller	700	7-1/2	4-5/8	6-1/2	B6AS8M-7	12260
8	2	Seal Roller	900	9-1/2	6	7-1/2	B8AS8M-7	12261

HONCHO/POLYURETHANE Tread Wheel. Tough, resilient polyurethane mechanically interlocked to husky die cast aluminum core for extra abuse conditions.

5	2	Seal Roller	900	6-1/2	3-15/16	6-1/2	B5AS3P-7	12803
6	2	Seal Roller	900	7-1/2	4-5/8	7-1/2	B6AS3P-7	12813
8	2	Seal Roller	900	9-1/2	6	9	B8AS3P-7	12823

CANAPHIN WHEEL Phenolic resin plastic reinforced with new low water absorption macerated canvas. High load capacity, impact strength, floor protection and easy, quiet rolling. Resistant to many chemicals, acids, solvents, and water solutions. Operating temperatures from -40°F to +300°F. Clean, non-marking wheel for use on hand pushed and power towed equipment on hard, smooth floors or carpet. Supplied standard with sealed roller bearing in wheel.

5	2	Seal Roller	900	6-1/2	3-15/16	6	B5AS8-7	12262
6	2	Seal Roller	900	7-1/2	4-5/8	7-1/2	B6AS8-7	12263
8	2	Seal Roller	900	9-1/2	6	8-1/2	B8AS8-7	12264

Bassick HONCHO 900

SWIVEL LOCK CASTERS

Swivel lock casters easily become rigid casters for easy trailing

SERIES AS SL4 5", 6", & 8" DIA. WHEELS

Hand operated plunger engages to lock swivel caster in any of four directions obtaining the easy trailing of rigid casters. When released, all swivel casters allow maximum freedom of travel for difficult paths.

Swivel: Supplied Standard with sealed swivel bearing to retain lubricant and exclude contaminants. Heat treat hardened bearing races for easier swiveling and long life.

Finish: Zinc Chromate for superior corrosion resistance.



8AS3P-7 SL4

Bolt hole spacing $2\frac{5}{8}'' \times 3\frac{5}{8}''$
 slotted to $3'' \times 3''$
 Mounting bolt dia. $\frac{3}{8}''$
 Top plate size $4'' \times 4\frac{1}{2}''$

WHEEL			SWIVEL CASTER					
Dia. In.	Tread Width In.	Bearing Type	Load Cap. Lbs.	Caster Height In.	Swivel Radius In.	Approx. Weight Lbs.	Bassick No.	Stand EDP No.

ALCORE/RUBBER TREAD WHEEL. Soft rubber tread bonded to aluminum core provides maximum floor and load protection, impact strength and quiet operation. Recommended for hand pushed or conveyor towed operation on hard floors. Supplied standard with sealed roller wheel bearing.

5	2	Seal Roller	450	6-1/2	3-15/16	6	5AS3R-7 SL4	12336
6	2	Seal Roller	500	7-1/2	4-5/8	7-1/2	6AS3R-7 SL4	12337
8	2	Seal Roller	600	9-1/2	6	10	8AS3R-7 SL4	12338

HONCHO/POLYURETHANE Tread Wheel. Tough, resilient polyurethane mechanically interlocked to husky die cast aluminum core for extra abuse conditions.

5	2	Seal Roller	900	6-1/2	3-15/16	6	5AS3P-7 SL4	12802
6	2	Seal Roller	900	7-1/2	4-5/8	7	6AS3P-7 SL4	12812
8	2	Seal Roller	900	9-1/2	6	9	8AS3P-7 SL4	12822

CANAPHIN WHEEL. Phenolic Plastic reinforced with macerated canvas for high load capacity, easy rolling, floor protection and resistance to many chemicals and temperature up to 300°F Use on hard floors and carpet.

5	2	Seal Roller	900	6-1/2	3-15/16	5-3/4	5AS8-7SL4	12325
6	2	Seal Roller	900	7-1/2	4-5/8	6-3/4	6AS8-7SL4	12330
8	2	Seal Roller	900	9-1/2	6	8	8AS8-7SL4	12334