

GP/GPR "GENERAL PURPOSE" SERIES CASTERS (formerly GN/GR Series)



600 lbs. Maximum Capacity

Top Plate: 3-3/8" x 4-1/8" Mounting Holes: 2-1/8" x 2-7/8" Slotted to 2-5/8" x 3-3/8" BHS 5/16" Hole Clearance

ALSO AVAILABLE IN STAINLESS STEEL (SEE PAGE 32)



GP-4150-EL-RB



GP/TLB-3150C-ES-HRB



GPR-4150-NY-RB

This medium duty caster is truly a beautiful product. Top plate size matches European standards. Swivels feature precision formed double ball raceways and standard head seals. The optional "Total Lock Brake" locks both the wheel and swivel with one press of the pedal. Simply kick to release. Rigids feature extreme forming for added strength. For medium duty applications nothing beats this caster.

NEW

Optional 4" x 4-1/2" Top Plate now available! (See below)

Wheel Diam.	OH	Swiv. Rad.
3"	4-1/16"	3"
4"	5-1/16"	3-1/2"
5"	6-1/8"	4-1/4"
6"	7-1/8"	4-3/4"

Swivel Model Number	Rigid Model Number	Tread Width	Wheel Type	Capacity (lbs.)	Bearing Type	Weight (Approx)	
						Swivel	Rigid
3" Diameter Wheels							
GP-3125-BAL	GPR-3125-BAL	1-1/4"	Phenolic	300	Plain	2.0	1.5
GP-3125-BST	GPR-3125-BST	1-1/4"	Cast Steel	300	Plain	3.0	2.5
GP-3125C-BST-RB	GPR-3125C-BST-RB	1-1/4"	Cast Steel (Crowned)	300	Roller	3.5	3.0
GP-3125-UN-BB	GPR-3125-UN-BB	1-1/4"	Star-Tech Urethane	250	Ball Bearing	2.0	1.5
GP-3125-MR	GPR-3125-MR	1-1/4"	Multi-Purpose Rubber	210	Plain	2.0	1.5
GP-3125-EL-BB	GPR-3125-EL-BB	1-1/4"	Eliminator Grey Rubber	200	Ball Bearing	2.0	1.5
GP-3125-NL	GPR-3125-NL	1-1/4"	Ny-Lite	275	Plain	2.0	1.5
GP-3125-WNL	GPR-3125-WNL	1-1/4"	White Poly-Olefin	275	Plain	2.0	1.5
GP-3150-BAL-RB	GPR-3150-BAL-RB	1-1/2"	Phenolic	300	Roller	2.5	2.0
GP-3150-BST-RB	GPR-3150-BST-RB	1-1/2"	Cast Steel	300	Roller	4.0	3.5
CONSULT FACTORY	GPR-3150-VG-RB	1-1/2"	Cast Steel (V-Groove)	300	Roller	3.5	3.0
GP-3150-UC-RB	GPR-3150-UC-RB	1-1/2"	Urethane on Cast	300	Roller	3.5	3.0
GP-3150C-ES-HRB	GPR-3150C-ES-HRB	1-1/2"	Solid Elastomer (Crowned)	300	HD Roller	2.5	2.0
GP-3150-NY-RB	GPR-3150-NY-RB	1-1/2"	White Nylon	300	Roller	2.5	2.0
GP-3150-EAS-PBB	GPR-3150-EAS-PBB	1-1/2"	Anti-Static Elastomer	300	Precision Ball	2.5	2.0
GP-080-HTM-HL	GPR-080-HTM-HL	35mm	Hi-Temp Monolithic	220	Hi-Lex	2.0	1.5
4" Diameter Wheels							
GP-4125-BAL	GPR-4125-BAL	1-1/4"	Phenolic	300	Plain	2.5	2.0
GP-4125-BST	GPR-4125-BST	1-1/4"	Cast Steel	400	Plain	3.5	3.0
GP-4125-UN-BB	GPR-4125-UN-BB	1-1/4"	Star-Tech Urethane	250	Ball Bearing	2.5	2.0
GP-4125-EL-BB	GPR-4125-EL-BB	1-1/4"	Eliminator Grey Rubber	220	Ball Bearing	2.5	2.0
GP-4125-NL	GPR-4125-NL	1-1/4"	Ny-Lite	300	Plain	2.0	1.5
GP-4125-WNL	GPR-4125-WNL	1-1/4"	White Poly-Olefin	300	Plain	2.0	1.5
GP-4138-MR	GPR-4138-MR	1-3/8"	Multi-Purpose Rubber	300	Plain	3.0	2.5
GP-4150-BAL-RB	GPR-4150-BAL-RB	1-1/2"	Phenolic	400	Roller	2.5	2.0
GP-4150-HT-RB	GPR-4150-HT-RB	1-1/2"	Hi-Temp Phenolic	400	Roller	2.5	2.0
GP-4150-BST	GPR-4150-BST	1-1/2"	Cast Steel	400	Plain	4.5	4.0
GP-4150-BST-RB	GPR-4150-BST-RB	1-1/2"	Cast Steel	400	Roller	4.5	4.0
CONSULT FACTORY	GPR-4150-VG-RB	1-1/2"	Cast Steel (V-Groove)	400	Roller	4.5	4.0
GP-4150-UN-RB	GPR-4150-UN-RB	1-1/2"	Star-Tech Urethane	400	Roller	2.5	2.0
GP-4150-UC-RB	GPR-4150-UC-RB	1-1/2"	Urethane on Cast	400	Roller	3.5	3.0
GP-4150C-ES-HRB	GPR-4150C-ES-HRB	1-1/2"	Solid Elastomer (Crowned)	400	HD Roller	2.5	2.0
GP-4150-MR-RB	GPR-4150-MR-RB	1-1/2"	Multi-Purpose Rubber	400	Roller	3.0	2.5
GP-4150-EL-RB	GPR-4150-EL-RB	1-1/2"	Eliminator Grey Rubber	350	Roller	2.5	2.0
GP-4150-RMC-RB	GPR-4150-RMC-RB	1-1/2"	Rubber Moldon (H90)	400	Roller	4.0	3.5
GP-4150-NL-RB	GPR-4150-NL-RB	1-1/2"	Ny-Lite	400	Roller	2.5	2.0
GP-4150-NY-RB	GPR-4150-NY-RB	1-1/2"	White Nylon	400	Roller	2.5	2.0
GP-4150-EAS-PBB	GPR-4150-EAS-PBB	1-1/2"	Anti-Static Elastomer	400	Precision Ball	2.5	2.0
GP-100-HTM-HL	GPR-100-HTM-HL	35mm	Hi-Temp Monolithic	275	Hi-Lex	2.5	2.0

Swivel Model Number	Rigid Model Number	Tread Width	Wheel Type	Capacity (lbs.)	Bearing Type	Weight (Approx)	
						Swivel	Rigid
5" Diameter Wheels							
GP-5150-BAL-RB	GPR-5150-BAL-RB	1-1/2"	Phenolic	450	Roller	3.0	2.5
GP-5150-BST-RB	GPR-5150-BST-RB	1-1/2"	Cast Steel	450	Roller	4.5	4.0
GP-5150-UN-RB	GPR-5150-UN-RB	1-1/2"	Star-Tech Urethane	450	Roller	2.5	2.0
GP-5150-UC-RB	GPR-5150-UC-RB	1-1/2"	Urethane on Cast	450	Roller	4.5	4.0
GP-5150C-ES-HRB	GPR-5150C-ES-HRB	1-1/2"	Solid Elastomer (Crowned)	450	HD Roller	3.0	2.5
GP-5150-MR-RB	GPR-5150-MR-RB	1-1/2"	Multi-Purpose Rubber	450	Roller	3.5	3.0
GP-5150-EL-RB	GPR-5150-EL-RB	1-1/2"	Eliminator Grey Rubber	400	Roller	2.5	2.0
GP-5150-RMC-RB	GPR-5150-RMC-RB	1-1/2"	Rubber Moldon (H90)	450	Roller	4.5	4.0
GP-5150-NL-RB	GPR-5150-NL-RB	1-1/2"	Ny-Lite	450	Roller	2.5	2.0
GP-5150-NY-RB	GPR-5150-NY-RB	1-1/2"	White Nylon	450	Roller	3.0	2.5
GP-5150-EAS-PBB	GPR-5150-EAS-PBB	1-1/2"	Anti-Static Elastomer	450	Precision Ball	3.0	2.5
GP-125-HTM-HL	GPR-125-HTM-HL	40mm	Hi-Temp Monolithic	330	Hi-Lex	3.0	2.5
6" Diameter Wheels							
GP-6150-BAL-RB	GPR-6150-BAL-RB	1-1/2"	Phenolic	600	Roller	4.0	3.0
GP-6150-UN-RB	GPR-6150-UN-RB	1-1/2"	Star-Tech Urethane	600	Roller	3.5	2.5
GP-6150-UC-RB	GPR-6150-UC-RB	1-1/2"	Urethane on Cast	600	Roller	5.5	4.5
GP-6150-MR-RB	GPR-6150-MR-RB	1-1/2"	Multi-Purpose Rubber	550	Roller	4.0	3.0
GP-6150-EL-RB	GPR-6150-EL-RB	1-1/2"	Eliminator Grey Rubber	500	Roller	3.5	2.5
GP-6150-RMC-RB	GPR-6150-RMC-RB	1-1/2"	Rubber Moldon (H90)	600	Roller	5.5	4.5
GP-6150-NL-RB	GPR-6150-NL-RB	1-1/2"	Ny-Lite	600	Roller	3.0	2.0
GP-6150-NY-RB	GPR-6150-NY-RB	1-1/2"	White Nylon	600	Roller	3.5	2.5

Options: (1) Total Lock Brake available on swivels only. Add code 'TLB' to model number (eg. GP/TLB-5150-EL-RB)
 (2) Optional 4" x 4-1/2" top plate available. Add code 'STP' to model number. (eg. GP/STP-6150-BAL-RB)
 (3) Delrin Bearing. Substitute 'DEL' for 'RB' or 'BB' in Model Number (eg. GP-3150-BAL-DEL)

TYPES OF BRAKES

Bestway offers a variety of brake styles with our casters. Each type offers it's own advantages over other types as described below. Our experienced sales staff can assist you in selecting the proper brake type for your specific application. Not all brake types are available with every caster series or wheel type. Consult the options list following each series listing in this catalogue for the brake types offered with that series.

Side Pedal Brake (BR):

This pedal brake is mounted on the side of the caster by way of the axle. Pushing the pedal causes the brake to activate against the side of the wheel preventing the wheel from turning. This is the most economical brake type available.



BW/BR-5150-BAL-RB

Total Lock Brake (TLB):

This pedal brake is mounted on the trailing edge of swivel casters only. Depressing the pedal causes the brake to activate against the wheel face, stopping it from turning. At the same time, the swivel lock mechanism activates against the raceway of the caster preventing the caster from swiveling. These brakes may increase the swivel radius on some casters.



GP/TLB-3150C-ES-HRB

T-Handle Brake (TBR):

This simple, yet effective brake consists of a metal "T" handle threaded into a hole in the side of the caster leg. Turning the handle causes it to activate against the side of the wheel preventing it from turning. This is especially effective on heavier casters where a cam style side pedal brake may not provide sufficient locking pressure.



HX/TBR-6300-DU-RB

Poly-Cam Brake (PCB):

This highly effective brake is ideal for heavier casters where maximum braking power is required. A poly-cam handle mounted on the caster is used to activate a brake plunger firmly against the face of the wheel preventing it from turning. These brakes may increase the swivel radius on some casters.



TWLE/PCB-5200-UBA-PBB