


Series: LS-SETH, BS-SETH

Welded steel heavy duty swivel and fixed castors, extra strong swivel head design

 500 - 1350 kg




Brackets: LS/BS Series - Very rugged welded steel construction, swivel bracket with axial grooved ball bearing DIN 711 and tapered roller bearing DIN 720 in the swivel head, dust and splash-proof. Fitted grease nipple, welded very strong, bolted and secured central kingpin, bolted wheel axle, zinc-plated - yellow passivated.
Top plate drawings: Page 71 and 72.
Detailed description: Page 64 and 77.

Wheels: SETH Series - Treads: Made of Blicke Extrathane® polyurethane, firmly bonded, colour light brown, non-marking, 92° shore A, elastic, abrasion-resistant, high cut and tear propagation resistance, non-staining, floor-saving, low-noise operation, low rolling resistance, very good chemical connection with the wheel centre.
Wheel centres: Strong welded steel construction with double-welded tubular steel hub, ball bearing.
Lacquered - colour silver.


Special Blicke wheel centre construction, very high stability, elegant and smooth design.

Detailed description: Page 224 and 45.

Swivel castors	Fixed castors	Swivel castors with "stop-top" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swvl castor [mm]
Ref. No.	Ref. No.	Ref. No.									
LS-SETH 125K	BS-SETH 125K	LS-SETH 125K-ST	125	50	500	Ball bearing	170	140 x 110	105 x 75-80	11	50
LS-SETH 150K	BS-SETH 150K	LS-SETH 150K-ST	150	50	650	Ball bearing	200	140 x 110	105 x 75-80	11	55
LS-SETH 160K	BS-SETH 160K	LS-SETH 160K-ST	160	50	700	Ball bearing	205	140 x 110	105 x 75-80	11	55
LS-SETH 200K	BS-SETH 200K	LS-SETH 200K-ST	200	50	1000	Ball bearing	245	140 x 110	105 x 75-80	11	60
LS-SETH 250K	BS-SETH 250K	LS-SETH 250K-ST	250	60	1350	Ball bearing	305	175 x 140	140 x 105	14	75



Variants / Accessories



	With directional lock 2 x 180°	With directional lock 4 x 90°	Truck lock
Technical description page	78	78	78
Ref. No. extension	-RI2	-RI4	FF160 / FF200
Available for wheel Ø [mm]	All sizes	Upon request	160 - 200 Rest upon request