



### FEATURES

Dual wheel casters are designed for heavy duty, extra heavy duty and super duty applications. Constructed of our popular hot forged C-1045 steel swivel sections, these dual wheel casters offer the highest possible capacity at the lowest overall height. The casters feature legs that are welded to a unique skirt design for greater strength and longevity.

### BENEFITS

The large footprint provides for a greater distribution of load on the floor. Additionally, the larger casters have a vertical center leg to further enhance the load distribution. Less effort is needed when changing direction as the design allows the wheels to rotate at variable rates to compensate for the shorter radius in the arc.

### APPLICATIONS

Excellent for tow lines, industrial platform trucks, rugged industrial functions and other severe abuse applications.



2-99-22801-69-1 shown

### OPTIONS

- Brakes
  - Poly Cam: P
  - Face Contact: F
  - Double Side: DS
- Swivel Locks
  - Factory Installed: L
  - Demountable: DL
- Sealed Swivel: SSW
- Toe Guard: TG

**All casters available in kingpinless style, consult factory.**

WHEEL		CAPACITY			PART NUMBER				
-------	--	----------	--	--	-------------	--	--	--	--

	Dia.	Width	Material	Roller Bearing	Tapered	OAH	Swivel Lead	Straight Roller	Precision Tapered	Series	Wt.

4	1.50	Phenolic Resin	1,200			5.62	1.50	52-04101-30-1		50	9.5
4	1.50	Polyurethane	1,350			5.62	1.50	52-04101-60-1		50	11.0
5	1.50	Phenolic Resin	1,200			6.50	1.75	52-05101-30-1		50	10.5
5	1.50	Polyurethane	1,400			6.50	1.75	52-05101-60-1		50	11.5
6	2.00	Cast Iron	1,500			7.50	2.25	52-06201-10-1		50	21.0
6	2.00	Forged Steel	1,500			7.50	2.25	52-06201-20-1		50	20.0
6	2.00	Phenolic Resin	1,500			7.50	2.25	52-06201-30-1		50	13.0
6	2.00	Polyurethane	1,500			7.50	2.25	52-06201-60-1		50	18.0
6	2.00	Mold on Rubber	820			7.50	2.25	52-06201-70-1		50	12.5
3	1.50	Polyurethane	900			5.25	1.50	62-03101-60-1		60	9.0
4	1.50	Phenolic Resin	1,200			5.62	1.50	62-04101-30-1		60	9.5
4	1.50	Polyurethane	1,350			5.62	1.50	62-04101-60-1		60	11.0
5	1.50	Phenolic Resin	1,200			6.50	1.75	62-05101-30-1		60	10.5
5	1.50	Polyurethane	1,400			6.50	1.75	62-05101-60-1		60	11.5
4	1.50	Forged Steel	2,000			5.50	2.25	66-04101-20-1		65	14.0
4	2.00	Phenolic Resin	1,600			5.50	2.25	66-04201-30-1		65	11.0
4	2.00	Polyurethane	1,500			5.50	2.25	66-04201-60-1		65	12.0
5	2.00	Forged Steel	2,000			6.50	2.25	66-05201-20-1		65	17.0
5	2.00	Phenolic Resin	2,000			6.50	2.25	66-05201-30-1		65	11.5
5	2.00	Polyurethane	2,000			6.50	2.25	66-05201-60-1		65	15.0
5	2.00	Mold on Rubber	700			6.50	2.25	66-05201-70-1		65	13.0
6	2.00	Cast Iron	2,000			7.50	2.25	66-06201-10-1		65	21.0
6	2.00	Forged Steel	2,000			7.50	2.25	66-06201-20-1		65	20.0
6	2.00	Phenolic Resin	2,000			7.50	2.25	66-06201-30-1		65	13.0
6	2.00	Polyurethane	2,000			7.50	2.25	66-06201-60-1		65	18.0
6	2.00	Mold on Rubber	820			7.50	2.25	66-06201-70-1		65	12.5



CASTER CONCEPTS

# DUAL WHEEL CASTERS

## 17,000 maximum capacity LBS

DUAL WHEEL CASTERS 17,000 lbs maximum capacity

### WHEEL CAPACITY PART NUMBER

Dia.	Width	Material	Roller	Tapered	OAH	Swivel Lead	Straight Roller	Precision Tapered	Series	Wt.							
8	2.00	Cast Iron	2,000		10.12	2.25	66-08201-10-1		65	26.0							
8	2.00	Phenolic Resin	2,000		10.12	2.25	66-08201-30-1		65	18.0							
8	2.00	Polyurethane	2,000		10.12	2.25	66-08201-60-1		65	25.0							
8	2.00	Mold on Rubber	1,000		10.12	2.25	66-08201-70-1		65	35.0							
6	2.50	Mold on Rubber	1,080	1,080	8.00	2.25	72-06251-70-1	72-06259-70-1	70	37.0							
6	2.50	Polyurethane	3,500	3,500	8.00	2.25	72-06251-60-1	72-06259-60-1	70	40.0							
6	2.50	Phenolic Resin	3,500		8.00	2.25	72-06251-30-1		70	26.0							
6	2.50	Cast Iron	3,500	3,500	8.00	2.25	72-06251-10-1	72-06259-10-1	70	37.0							
8	2.50	Mold on Rubber	1,340	1,340	10.50	2.50	72-08251-70-1	72-08259-70-1	70	38.0							
8	2.50	Polyurethane	3,500	3,500	10.50	2.50	72-08251-60-1	72-08259-60-1	70	40.0							
8	2.50	Phenolic Resin	3,500		10.50	2.50	72-08251-30-1		70	30.0							
10	2.50	Mold on Rubber	1,550	1,550	12.50	2.50	72-10251-70-1	72-10259-70-1	70	42.0							
10	2.50	Polyurethane	3,500	3,500	12.50	2.50	72-10251-60-1	72-10259-60-1	70	52.0							
10	2.50	Phenolic Resin	3,500	3,500	12.50	2.50	72-10251-30-1	72-10259-30-1	70	35.0							
12	2.50	Mold on Rubber	1,800	1,800	14.00	2.50	72-12251-70-1	72-12259-70-1	70	51.0							
12	2.50	Polyurethane	3,500	3,500	14.00	2.50	72-12251-60-1	72-12259-60-1	70	58.0							
12	2.50	Phenolic Resin	3,500	3,500	14.00	2.50	72-12251-30-1	72-12259-30-1	70	43.0							
6	3.00	Polyurethane	4,100	4,100	9.00	2.50	82-06301-60-1	82-06309-60-1	80	44.0							
6	3.00	Phenolic Resin	4,000	4,000	9.00	2.50	82-06301-30-1	82-06309-30-1	80	39.0							
6	3.00	Forged Steel	5,000	5,000	9.00	2.50	82-06301-20-1	82-06309-20-1	80	65.0							
8	3.00	Polyurethane	5,000	5,000	11.00	2.50	82-08301-60-1	82-08309-60-1	80	50.0							
8	3.00	Phenolic Resin	5,000	5,000	11.00	2.50	82-08301-30-1	82-08309-30-1	80	40.0							
8	3.00	Forged Steel	5,000	10,000	11.00	2.50	82-08301-20-1	86-08309-20-1	80	62.0							
8	3.00	Cast Iron	5,000	5,000	11.00	2.50	82-08301-10-1	82-08309-10-1	80	62.0							
10	3.00	Polyurethane	6,000	6,000	13.00	2.50	86-10301-60-1	86-10309-60-1	85	58.0							
10	3.00	Phenolic Resin	5,800	5,800	13.00	2.50	86-10301-30-1	86-10309-30-1	85	45.0							
10	3.00	Forged Steel	10,000	10,000	13.00	2.50	86-10301-21-1	86-10309-21-1	85	81.0							
10	3.00	Cast Iron	6,000	6,000	13.00	2.50	86-10301-10-1	86-10309-10-1	85	71.0							
6	3.00	Forged Steel	11,000	17,000	9.00	2.50	96-06301-20-1	96-06309-20-1	95	85.0							
6	5.00	H.D. Polyurethane		7,400	9.00	2.50		96-06509-65-1	95	90.0							
8	3.00	H.D. Polyurethane		6,200	11.00	2.50		96-08309-65-1	95	75.0							
8	4.00	Polyurethane	7,600	7,600	11.00	2.50	96-08401-60-1	96-08409-60-1	95	75.0							
8	4.00	H.D. Forged Steel		17,000	11.00	2.50		96-08409-21-1	95	112.0							
10	3.00	H.D. Polyurethane	7,400	7,400	13.00	2.50	96-10301-65-1	96-10309-65-1	95	88.0							
10	3.00	Laminated Phenolic	6,000	6,000	13.00	2.50	96-10301-35-1	96-10309-35-1	95	67.0							
10	3.00	H.D. Forged Steel	12,000	13,000	13.00	2.50	96-10301-21-1	96-10309-21-1	95	123.0							
10	4.00	H.D. Forged Steel		17,000	13.00	2.50		96-10409-21-1	95	140.0							
10	4.00	H.D. Polyurethane	10,000	10,000	13.00	2.50	96-10401-65-1	96-10409-65-1	95	103.0							
10	4.00	Polyurethane	8,400	8,400	13.00	2.50	96-10401-60-1	96-10409-60-1	95	90.0							
10	5.00	H.D. Polyurethane	12,000	12,000	13.00	2.50	96-10501-65-1	96-10509-65-1	95	103.0							
12	3.00	H.D. Polyurethane	7,700	7,700	15.50	2.50	96-12301-65-1	96-12309-65-1	95	108.0							
12	3.50	Laminated Phenolic	8,500	8,500	15.50	2.50	96-12351-35-1	96-12359-35-1	95	97.0							
12	4.00	H.D. Polyurethane	11,000	11,000	15.50	2.50	96-12401-65-1	96-12409-65-1	95	120.0							
12	4.00	70D H.L. Polyurethane	13,000	13,000	15.50	2.50	96-12401-67-1	96-12409-67-1	95	100.0							
12	5.00	H.D. Polyurethane	12,500	12,500	15.50	2.50	96-12501-65-1	96-12509-65-1	95	150.0							
12	5.00	70D H.L. Polyurethane	15,000	15,000	15.50	2.50	96-12501-67-1	96-12509-67-1	95	130.0							
16	5.00	H.D. Polyurethane	16,000	16,000	19.00	4.00		96-16509-65-1	95	200.0							
16	5.00	H.D. Polyurethane	16,000	17,000	19.00	4.00		96-16509-67-1	95	200.0							
18	5.00	H.D. Polyurethane	17,000	17,000	23.00	4.00		96-18509-65-1	95	220.0							
18	5.00	H.D. Polyurethane	17,000	17,000	23.00	4.00		96-18509-67-1	95	220.0							

Capacity listed is for manual operation. For powered operations, consult factory.

Part Numbers listed are for the swivel casters. For rigid casters, change the last digit from 1 to 2 (i.e. 96-12409-65-2)

See series codes for top plate and bolt hole dimensions.

All dimensions are in inches. All weights are in pounds.