# Kick Stop<sup>®</sup> Casters





### **Standard Features**

- Foot brake easily engaged; mechanically locks both swivel and wheel rotation
- Strong pressure diecast metal construction for lasting performance and maximum reliability
- Precision axle built to exacting tolerances for smooth operation and extended service life
- Aluminum die cast body and wheel centers
- Standard finish is white or ball burnished and lacquered

### **Kick Stop Casters**

Colson Kick Stop casters give you the benefits of twin-wheel design with the convenience of a foot brake to lock both wheel and swivel simultaneously. This modern design features two wheels that spin independently of each other for easier turning in tight spots and for improved stability. Custom colors are available to match your equipment (Consult factory).

#### Applications

- · Medical and diagnostic equipment
- · Computer equipment
- Electronic equipment
- · High-tech products

## Kick Stop Casters · Capacity up to 175 lbs

Wheel Diameter	Tread Width	Capacity Per Caster	Wheel Type	Bearing	Model Number			Approx.	Load	Swivel
					Kick Stop	Free Swivel	Fitting Type	Wt.ea.	Height	Radius
<b>3"</b> <sup>75mm</sup>	19/32'' (15mm)	132lbs (70kg)	Grey Polyurethane	Delrin	2.3502.409.8	2.3504.409.8	Threaded M10x1.5mm x15mm long	.77 lb (.35kg)	3 <sup>37</sup> / <sub>64</sub> '' (91mm)	2 <sup>9</sup> /16'' (65mm)
			Black Polyurethane	Delrin	2.3502.409.7	2.3504.409.7				
<b>4"</b> 100mm	19/32'' (15mm)	132lbs (70kg)	Black Rubber (Anti-static)	Roller	2.4502.409.4	2.4504.409.4	Threaded M12x1.75mm x20mm long	1.78 lbs (.81kg)	4 <sup>3</sup> /4'' (120mm)	Total Lock 3 <sup>9</sup> /16" (90mm) Swive 3 <sup>1</sup> /8" (79mm)
			Grey Rubber	Roller Delrin	2.4502.409.1 2.4502.401.1	2.4504.409.1 2.4504.401.1				
<b>5"</b> 125mm	5/8'' (16mm)	175lbs (80kg)	Black Rubber (Anti-static)	Roller	2.5502.409.4	2.5504.409.4	Threaded M16x2mm x20mm long	3 lbs (1.36kg)	5 <sup>13</sup> / <sub>16</sub> '' (148mm)	Total Lock and Swivel 4 <sup>3</sup> /16'' (106mm)
			Grey Rubber	Roller Delrin	2.5502.409.1 2.5502.401.1	2.5504.409.1 2.5504.401.1				

**Note:** Kick Stop casters have improved load capacity with harder wheel types. Consult factory. Changes to above caster specifications can be considered to suit individual requirements. Such modifications may depend on the size of order and are subject to special quotation and delivery. All specifications and dimensions are accurate for present manufacture but subject to change without notice. Kick Stop casters are covered by worldwide patents and designs.