## **291** Series

## **General Duty**

Capacity to 400 pounds each

## FEATURES

- Design: low profile design for lower equipment height.
- Finish: bright zinc plating to resist rust and corrosion.
- Swivel Construction: large raceways are deeply embossed for extra strength and bearing surface. Special precision kingpin engineered for thrust absorption and long service life.

✓ Axle: Nut and bolt axles.

2" wheels use 1/4" diameter axle.  $2^{1}/2$ " wheels use 5/16" diameter axle. 3" wheels use 3/6" axle. 4" wheels use 7/16" diameter axle.

CASTER OPTIONS✓ Brake: available on

quantity orders–consult factory.



## **MOUNTING OPTIONS**

Swivel Cas Wheel Diameter (Inches)	sters: Top Plate Size	Bolt Hole Spacing	Mounting Bolt Size		
2	1-7/8" x 2-5/8"	15/16" x 2-1/8"	1/4		
2-1/2	2-5/8" x 3-3/4"	1-3/4" x 3"	5/16		
3	3-1/8" x 4-1/8"	2-3/8" x 3-7/16"	5/16		
4 4" x 5"		3" x 4"	3/8		
Rigid Cast	ers:				

1	nigiu vasiers.							
	2	1-7/8" x 2-5/8"	15/16" x 2-1/8"	1/4				
	2-1/2	2-1/8" x 4-3/8"	1-1/16" x 3-15/32"	5/16				
	3	2-1/2" x 4-7/8"	2-3/8" x 3-7/16"	5/16				
	4	3-1/4" x 6-1/4"	1-3/4" x 5"	3/8				

Wheel Diameter (Inches)	Tread Width (Inches)	Wheel Type	Bearing	Capacity (Pounds)		Rigid Caster Model Number 292 Series	Approximate Weight (Pounds)	Load Height (Inches)	Swivel Radius (Inches)
	. 1	CUSHION GREY / SOLID RUBBER	SINTERED	90	2-291-103	2-292-103	3/4	2 1/2	1 11/16
2		HARD TREAD / SOLID RUBBER	SINTERED	125	2-291-104	2-292-104			
		CAST IRON	PLAIN	125	2-291-120	2-292-120			
	<b>2</b> 1 1/8	CUSHION GREY / SOLID RUBBER	SINTERED	90	2-1/2-291-103	2-1/2-292-103	1 3/4	3 1/4	2 <sup>3/</sup> 16
21/2		HARD TREAD / SOLID RUBBER	SINTERED	125	2-1/2-291-104	2-1/2-292-104			
- / -		CAST IRON	PLAIN	125	2-1/2-291-120	2-1/2-292-120			
	1 9/32	CUSHION GREY / SOLID RUBBER	DELRIN	140	3-291-105	3-292-105	1 3/8	3 13/16	2 <sup>5/</sup> 16
•		HARD TREAD / SOLID RUBBER	DELRIN	180	3-291-106	3-292-106			
3	<b>3</b> 1 1/4	CAST IRON	PLAIN	250	3-291-120	3-292-120			
		POLYOLEFIN	PLAIN	250	3-291-521	3-292-521	2		
		CUSHION GREY / SOLID RUBBER	SINTERED	240	4-291-109	4-292-109			
	1 5/8	HARD TREAD / SOLID RUBBER	ROLLER	240	4-291-210	4-292-210	3 1/2	5	2 <sup>15/</sup> 16
_		HARD TREAD / SOLID RUBBER	SINTERED	400	4-291-110	4-292-110			
4		CUSHION GREY / SOLID RUBBER	ROLLER	400	4-291-209	4-292-209			
	1 1/2	CAST IRON	PLAIN	400	4-291-130	4-292-130	4 1/2		
		CAST IRON	ROLLER	400	4-291-230	4-292-230			