

NEOTEQ (CN) COMFORT ROLL

SWIVEL/GRIP RING/THREADED/
HOLLOW KINGPIN

FREE SWIVEL • TOTAL LOCK



APPLICATIONS

- Laboratory Equipment
- IV Stands
- Mobile Computer Stands
- Medical Equipment

FEATURES

- Bright Chrome Finish
- Matching Chrome Thread Guards for wheels
- Non-Marking Soft-Neoprene Rubber wheels
- Dual Ball Swivel Raceways for added strength
- Total Lock Brake models lock both swivel and wheel
- Precision ball bearings in wheels for easier rollability
- Upper raceway seal to prevent dirt and dust build-up

Our Chrome NeoTeq series are designed to provide your equipment with a smooth and quiet roll.

SWIVEL TOP PLATE MODELS

| Wheel Diameter (Inches) | Tread Width (Inches) | Wheel Description | Capacity (Lbs) | Load Height Inches (mm) | Swivel Radius Inches (mm) | Wheel Bearing | Model Number |
|-------------------------|----------------------|-------------------|----------------|-------------------------|---------------------------|----------------|----------------------|
| 2 | 1 | Neoprene Rubber | 125 | 2-15/16" (75) | 2" (51) | Precision Ball | CN-02NRP-100-SW-TP02 |
| 3 | 1 | Neoprene Rubber | 175 | 4-5/32" (105) | 2-13/16" (71) | Precision Ball | CN-03NRP-100-SW-TP02 |



SWIVEL PLATE TOTAL LOCK MODELS

(LOCKS WHEEL AND SWIVEL)

| Wheel Diameter (Inches) | Tread Width (Inches) | Wheel Description | Capacity (Lbs) | Load Height Inches (mm) | Swivel Radius Inches (mm) | Wheel Bearing | Model Number |
|-------------------------|----------------------|-------------------|----------------|-------------------------|---------------------------|----------------|----------------------|
| 2 | 1 | Neoprene Rubber | 125 | 2-15/16" (75) | 2" (51) | Precision Ball | CN-02NRP-100-TL-TP02 |
| 3 | 1 | Neoprene Rubber | 175 | 4-5/32" (105) | 2-13/16" (71) | Precision Ball | CN-03NRP-100-TL-TP02 |




FITTINGS

Swivel Top Plate Fitting Pattern

2" diameter caster: 13/16" x 1-1/4" through 1-7/8" slotted

3" diameter caster: 13/16" x 1-7/8"



NEOTEQ (CN) COMFORT ROLL

GRIP RING STEM MODELS

| Wheel Diameter (Inches) | Tread Width (Inches) | Wheel Description | Capacity (Lbs) | Load Height Inches (mm) | Swivel Radius Inches (mm) | Wheel Bearing | Model Number |
|-------------------------|----------------------|-------------------|----------------|-------------------------|---------------------------|----------------|----------------------|
| 2 | 1 | Neoprene Rubber | 125 | 2-11/16" (68) | 2" (51) | Precision Ball | CN-02NRP-100-SW-GR01 |
| 3 | 1 | Neoprene Rubber | 175 | 4" (102) | 2-13/16" (71) | Precision Ball | CN-03NRP-100-SW-GR01 |



GRIP RING STEM TOTAL LOCK MODELS

(LOCKS WHEEL AND SWIVEL)

| | | | | | | | |
|---|---|-----------------|-----|---------------|---------------|----------------|----------------------|
| 2 | 1 | Neoprene Rubber | 125 | 2-11/16" (68) | 2" (51) | Precision Ball | CN-02NRP-100-TL-GR01 |
| 3 | 1 | Neoprene Rubber | 175 | 4" (102) | 2-13/16" (71) | Precision Ball | CN-03NRP-100-TL-GR01 |

THREADED STEM MODELS

| Wheel Diameter (Inches) | Tread Width (Inches) | Wheel Description | Capacity (Lbs) | Load Height Inches (mm) | Swivel Radius Inches (mm) | Wheel Bearing | Model Number |
|-------------------------|----------------------|-------------------|----------------|-------------------------|---------------------------|----------------|----------------------|
| 3 | 1 | Neoprene Rubber | 175 | 4" (102) | 2-13/16" (71) | Precision Ball | CN-03NRP-100-SW-TS06 |



THREADED STEM TOTAL LOCK MODELS

(LOCKS WHEEL AND SWIVEL)

| | | | | | | | |
|---|---|-----------------|-----|----------|---------------|----------------|----------------------|
| 3 | 1 | Neoprene Rubber | 175 | 4" (102) | 2-13/16" (71) | Precision Ball | CN-03NRP-100-TL-TS06 |
|---|---|-----------------|-----|----------|---------------|----------------|----------------------|

HOLLOW KINGPIN MODELS

| Wheel Diameter (Inches) | Tread Width (Inches) | Wheel Description | Capacity (Lbs) | Load Height Inches (mm) | Swivel Radius Inches (mm) | Wheel Bearing | Model Number |
|-------------------------|----------------------|-------------------|----------------|-------------------------|---------------------------|----------------|----------------------|
| 2 | 1 | Neoprene Rubber | 125 | 2-11/16" (68) | 2" (51) | Precision Ball | CN-02NRP-100-SW-HK04 |
| 3 | 1 | Neoprene Rubber | 175 | 4" (102) | 2-13/16" (71) | Precision Ball | CN-03NRP-100-SW-HK04 |

Recommended for use with 3/8" diameter fittings.



HOLLOW KINGPIN TOTAL LOCK MODELS

(LOCKS WHEEL AND SWIVEL)

| | | | | | | | |
|---|---|-----------------|-----|---------------|---------------|----------------|----------------------|
| 2 | 1 | Neoprene Rubber | 125 | 2-11/16" (68) | 2" (51) | Precision Ball | CN-02NRP-100-TL-HK04 |
| 3 | 1 | Neoprene Rubber | 175 | 4" (102) | 2-13/16" (71) | Precision Ball | CN-03NRP-100-TL-HK04 |

Recommended for use with 3/8" diameter fittings.

GRIP RING STEM


GR01



See fitting chart for additional options.

THREADED STEM

TS06



HOLLOW RIVET

Recommended for use with 3/8" diameter fittings.