

Load Capacity: 75 - 125lbs

Straight Stem Casters

FEATURES

- Double Ball Bearing Raceway Construction
 - Riveted Axle Assembly
 - Nickel Plate Finish standard on 2" & 2 1/2" casters
 - Zinc Plate Finish standard on 3" casters
 - Friction Brakes available on all sizes
 - Tread Brakes available on 3" Casters*
 - Hooded Casters available in 2" & 2 1/2" sizes* (zinc plated)
- *Minimum order quantities may apply.



TYPICAL APPLICATIONS

- Utility Tables
- Projector Stands
- Laundry Carts
- Laboratory Instrument Stands
- Bedside Tables

Wheel Diameter	Wheel Width	Plate Width	Plate Height	Load Capacity	Wheel Type	Caster Part Number	STD	Caster with Brake Part Number	STD	Swivel Radius	Offset
2"	15/16"	7/16" "DF"	1-7/8"	75 lbs.	Soft Rubber	39000-20DF-13PO	*	34000-20DF-13PO		2-9/16"	13/16"
					Conductive	39041-20DF-13PO	*	34041-20DF-13PO			
				90 lbs.	Hard Rubber	39010-20DF-13PO	*	34010-20DF-13PO	1-13/16"		
					Polyolefin	39020-20DF-13PO		34020-20DF-13PO			
2-1/2"	15/16"	7/16" "DF"	1-7/8"	90 lbs.	Soft Rubber	39000-25DF-13PO		34000-25DF-13PO		3-1/16"	13/16"
					Conductive	39041-25DF-13PO		34041-25DF-13PO	w/brake		
				100 lbs.	Hard Rubber	39010-25DF-13PO		34010-25DF-13PO	2-1/16"		
					Polyolefin	39020-25DF-13PO		34020-25DF-13PO			
3"	15/16"	7/16" "DF"	1-7/8"	100 lbs.	Soft Rubber	99000-30DF-23PO	*	94000-30DF-23PO		3-9/16"	2-1/2"
					Conductive	99041-30DF-23PO	*	94041-30DF-23PO	1"		
				125 lbs.	Hard Rubber	99010-30DF-23PO	*	94010-30DF-23PO			
					Polyolefin	99020-30DF-23PO		94020-30DF-23PO			

* Please inquire for additional caster variations.

Wheel Options



SOFT RUBBER
2", 2 1/2", 3"



HARD RUBBER
2", 2 1/2", 3"



POLYOLEFIN
2", 2 1/2", 3"



CONDUCTIVE
2", 2 1/2", 3"



COMOLDED URETHANE*
2", 2 1/2", 3"

*Minimums apply