

# Threaded Stem Casters


## FEATURES

- Double Ball Bearing Raceway Construction
  - Riveted Axle Assembly
  - Nickel Plate Finish standard on 2" & 2 1/2" casters
  - Zinc Plate Finish standard on 3" casters
  - Friction Brakes available on all sizes
  - Hooded Casters available in 2" & 2 1/2" sizes\* (zinc plated)
- \*Minimum order quantities may apply*



## WHEEL OPTIONS

- Soft Rubber 2", 2 1/2" & 3"
  - Hard Rubber 2", 2 1/2" & 3"
  - Polyolefin 2", 2 1/2" & 3"
  - Conductive 2", 2 1/2" & 3"
  - Polyurethane co-molded\* 2", 2 1/2" & 3"
- \*Minimum order quantities may apply*



### Threaded Stem

Threaded stems are used for direct attachment. These should always be securely fastened with a nut and not used for leveling. If a different height is required, a spacer should be inserted between the caster and the mounting area.

Wheel Diameter	Stem Diameter	Stem Length	Wheel Diameter	Load Capacity	Wheel Type	Caster Part Number	STD	Caster with Brake Part Number	STD	Swivel Radius	Offset	
2"	15/16"	5/16"-18	1/2"	75 lbs.	Soft Rubber	39000-20BA-1318	*	34000-20BA-1318	*	2-1/2"	13/16"	
					Conductive	39041-20BA-1318	34041-20BA-1318					
			"BA"	90 lbs.	Hard Rubber	39010-20BA-1318	34010-20BA-1318					
					Polyolefin	39020-20BA-1318	34020-20BA-1318					
			1"	75 lbs.	Soft Rubber	39000-20BC-1318	34000-20BC-1318					
					Conductive	39041-20BC-1318	34041-20BC-1318					
		"BC"	90 lbs.	Hard Rubber	39010-20BC-1318	34010-20BC-1318						
				Polyolefin	39020-20BC-1318	34020-20BC-1318						
		1-1/2"	75 lbs.	Soft Rubber	39000-20BE-1318	34000-20BE-1318						
				Conductive	39041-20BE-1318	34041-20BE-1318						
		"BE"	90 lbs.	Hard Rubber	39010-20BE-1318	34010-20BE-1318						
				Polyolefin	39020-20BE-1318	34020-20BE-1318						
	3/8"-16	5/16"-18	1/2"	75 lbs.	Soft Rubber	39000-20CA-1316	*	34000-20CA-1316	*	2-1/2"	2-3/8" w/brake	13/16"
					Conductive	39041-20CA-1316	34041-20CA-1316					
			"CA"	90 lbs.	Hard Rubber	39010-20CA-1316	34010-20CA-1316					
					Polyolefin	39020-20CA-1316	34020-20CA-1316					
			1"	75 lbs.	Soft Rubber	39000-20CC-1316	34000-20CC-1316					
					Conductive	39041-20CC-1316	34041-20CC-1316					
		"CC"	90 lbs.	Hard Rubber	39010-20CC-1316	34010-20CC-1316						
				Polyolefin	39020-20CC-1316	34020-20CC-1316						
		1-1/2"	75 lbs.	Soft Rubber	39000-20CE-1316	34000-20CE-1316						
				Conductive	39041-20CE-1316	34041-20CE-1316						
		"CE"	90 lbs.	Hard Rubber	39010-20CE-1316	34010-20CE-1316						
				Polyolefin	39020-20CE-1316	34020-20CE-1316						



				Load Capacity	Wheel Type	Caster Part Number	STD	Caster with Brake Part Number	STD		Swivel Radius	Offset	
2-1/2"	15/16"	5/16"-18	1/2" "BA"	90 lbs.	Soft Rubber	39000-25BA-1318	*	34000-25BA-1318		3"	2-3/8" w/brake	13/16"	
					Conductive	39041-25BA-1318		34041-25BA-1318					
				100 lbs.	Hard Rubber	39010-25BA-1318	*	34010-25BA-1318					
					Polyolefin	39020-25BA-1318		34020-25BA-1318					
			1" "BC"	90 lbs.	Soft Rubber	39000-25BC-1318	*	34000-25BC-1318	*				34041-25BC-1318
					Conductive	39041-25BC-1318		34010-25BC-1318					
				100 lbs.	Hard Rubber	39010-25BC-1318	*	34020-25BC-1318					
					Polyolefin	39020-25BC-1318		34000-25BE-1318					
			1-1/2" "BE"	90 lbs.	Soft Rubber	39000-25BE-1318	*	34041-25BE-1318					
					Conductive	39041-25BE-1318		34010-25BE-1318					
				100 lbs.	Hard Rubber	39010-25BE-1318	*	34020-25BE-1318					
					Polyolefin	39020-25BE-1318		34000-25CA-1316					
		3/8"-16	1/2" "CA"	90 lbs.	Soft Rubber	39000-25CA-1316	*	34000-25CA-1316	*		34041-25CA-1316		
					Conductive	39041-25CA-1316		34010-25CA-1316					
				100 lbs.	Hard Rubber	39010-25CA-1316	*	34020-25CA-1316					
					Polyolefin	39020-25CA-1316		34000-25CC-1316					
			1" "CC"	90 lbs.	Soft Rubber	39000-25CC-1316	*	34041-25CC-1316					
					Conductive	39041-25CC-1316	*	34010-25CC-1316					
				100 lbs.	Hard Rubber	39010-25CC-1316	*	34020-25CC-1316					
					Polyolefin	39020-25CC-1316		34000-25CE-1316					
			1-1/2" "CE"	90 lbs.	Soft Rubber	39000-25CE-1316	*	34041-25CE-1316					
					Conductive	39041-25CE-1316	*	34010-25CE-1316					
				100 lbs.	Hard Rubber	39010-25CE-1316	*	34020-25CE-1316					
					Polyolefin	39020-25CE-1316		99000-30BA-2318					
3"	15/16"	5/16"-18	1/2" "BA"	100 lbs.	Soft Rubber	99000-30BA-2318	*	94000-30BA-2318		3-9/16"	2-1/2"	1"	
					Conductive	99041-30BA-2318		94041-30BA-2318					
				125 lbs.	Hard Rubber	99010-30BA-2318	*	94010-30BA-2318					
					Polyolefin	99020-30BA-2318		94020-30BA-2318					
			1" "BC"	100 lbs.	Soft Rubber	99000-30BC-2318	*	94000-30BC-2318	*				94041-30BC-2318
					Conductive	99041-30BC-2318		94010-30BC-2318					
				125 lbs.	Hard Rubber	99010-30BC-2318	*	94020-30BC-2318					
					Polyolefin	99020-30BC-2318		94000-30BE-2318					
			1-1/2" "BE"	100 lbs.	Soft Rubber	99000-30BE-2318	*	94041-30BE-2318					
					Conductive	99041-30BE-2318	*	94010-30BE-2318					
				125 lbs.	Hard Rubber	99010-30BE-2318	*	94020-30BE-2318					
					Polyolefin	99020-30BE-2318		94000-30CA-2316					
		3/8"-16	1/2" "CA"	100 lbs.	Soft Rubber	99000-30CA-2316	*	94000-30CA-2316	*		94041-30CA-2316		
					Conductive	99041-30CA-2316		94010-30CA-2316					
				125 lbs.	Hard Rubber	99010-30CA-2316	*	94020-30CA-2316					
					Polyolefin	99020-30CA-2316		94000-30CC-2316					
			1" "CC"	100 lbs.	Soft Rubber	99000-30CC-2316	*	94041-30CC-2316					
					Conductive	99041-30CC-2316	*	94010-30CC-2316					
				125 lbs.	Hard Rubber	99010-30CC-2316	*	94020-30CC-2316					
					Polyolefin	99020-30CC-2316	*	94000-30CE-2316					
			1-1/2" "CE"	100 lbs.	Soft Rubber	99000-30CE-2316	*	94041-30CE-2316					
					Conductive	99041-30CE-2316	*	94010-30CE-2316					
				125 lbs.	Hard Rubber	99010-30CE-2316	*	94020-30CE-2316					
					Polyolefin	99020-30CE-2316	*						

\* Please inquire for additional caster variations.



# Threaded Stem Casters

## FEATURES

- Double Ball Bearing Raceway Construction
- Nut & Bolt Assembly
- Friction Brakes available on all sizes
- Zinc Plated Finish standard



## Threaded Stem Casters

Threaded stems are used for direct attachment. These should always be securely fastened with a nut and not used as a leveling device. If a different height is required, a spacer should be inserted between the caster and the mounting surface for support.

Wheel Diameter	Stem Diameter	Stem Length	Load Capacity	Wheel Type	Caster Part Number	STD	Caster with Brake Part Number	STD	Swivel Radius	Offset	
4"	15/16"	1/2"-13	125 lbs.	Soft Rubber	99001-40EC-2313	*	94001-40EC-2313	*	4-9/16"	3-1/2"	1-1/2"
				Conductive	99041-40EC-2313		94041-40EC-2313				
			150 lbs.	Hard Rubber	99011-40EC-2313	*	94011-40EC-2313				
				Polyolefin	99020-40EC-2313		94020-40EC-2313				
		1-1/2"	125 lbs.	Soft Rubber	99001-40EE-2313	*	94001-40EE-2313	*			
				Conductive	99041-40EE-2313	*	94041-40EE-2313				
			150 lbs.	Hard Rubber	99011-40EE-2313	*	94011-40EE-2313				
				Polyolefin	99020-40EE-2313		94020-40EE-2313				
5"	15/16"	7/16"	135 lbs.	Soft Rubber	99001-50EC-2313	*	94001-50EC-2313	*	5-9/16"	4"	1-1/2"
				Conductive	99041-50EC-2313		94041-50EC-2313				
			160 lbs.	Hard Rubber	99011-50EC-2313	*	94011-50EC-2313				
				Soft Rubber	99001-50EE-2313	*	94001-50EE-2313				
		1-1/2"	135 lbs.	Conductive	99041-50EE-2313	*	94041-50EE-2313				
				Hard Rubber	99011-50EE-2313	*	94011-50EE-2313				
			160 lbs.	Hard Rubber	99011-50EE-2313	*	94011-50EE-2313				

\* Please inquire for additional caster variations.

## Wheel Options



SOFT RUBBER

4" & 5"



HARD RUBBER

4" & 5"



POLYOLEFIN

4"



CONDUCTIVE

4" & 5"



COMOLDED URETHANE\*

5"

\*Miniums apply

# Threaded Stem Casters

## FEATURES

- Double Ball Bearing Raceway Construction
- Nut & Bolt Assembly
- Friction Brakes Available
- Zinc Plated Finish standard on all sizes



## Wheel Options

Soft Rubber: 3", 4" & 5"

Hard Rubber: 3", 4" & 5"

Polyolefin: 3"

Conductive: 3", 4" & 5"

Wheel Diameter	Stem Diameter	Stem Length	Load Capacity	Wheel Type	Caster Part Number	STD	Caster with Brake Part Number	STD	Swivel Radius	Offset
3"	1-1/4"	1/2"	175 lbs.	Soft Rubber	99001-31EC-2313	*	94001-31EC-2313	*	3-9/16"	1-1/4"
				Conductive	99041-31EC-2313	*	94041-31EC-2313	*		
				Hard Rubber	99011-31EC-2313	*	94011-31EC-2313	*		
				Polyolefin	99020-31EC-2313	*	94020-31EC-2313	*		
			270 lbs.	Soft Rubber	99001-31EE-2313	*	94001-31EE-2313	*	2-3/4"	w/o brake
				Conductive	99041-31EE-2313	*	94041-31EE-2313	*		
				Hard Rubber	99011-31EE-2313	*	94011-31EE-2313	*		
				Polyolefin	99020-31EE-2313	*	94020-31EE-2313	*		
4"	1-1/4"	1/2"	200 lbs.	Soft Rubber	99001-41EC-2313	*	94001-41EC-2313	*	4-3/4"	1-1/2"
				Conductive	99041-41EC-2313	*	94041-41EC-2313	*		
				Hard Rubber	99011-41EC-2313	*	94011-41EC-2313	*		
				Soft Rubber	99001-41EE-2313	*	94001-41EE-2313	*		
			280 lbs.	Conductive	99041-41EE-2313	*	94041-41EE-2313	*	3-9/16"	w/o brake
				Hard Rubber	99011-41EE-2313	*	94011-41EE-2313	*		
				Soft Rubber	99001-51EC-2313	*	94001-51EC-2313	*		
				Conductive	99041-51EC-2313	*	94041-51EC-2313	*		
5"	1-1/4"	1/2"	210 lbs.	Soft Rubber	99001-51EE-2313	*	94001-51EE-2313	*	5-13/16"	1-5/8"
				Conductive	99041-51EE-2313	*	94041-51EE-2313	*		
				Hard Rubber	99011-51EE-2313	*	94011-51EE-2313	*		
				Soft Rubber	99001-51EC-2313	*	94001-51EC-2313	*		
			290 lbs.	Conductive	99041-51EC-2313	*	94041-51EC-2313	*	4-1/8"	w/o brake
				Hard Rubber	99011-51EC-2313	*	94011-51EC-2313	*		
				Soft Rubber	99001-51EE-2313	*	94001-51EE-2313	*		
				Conductive	99041-51EE-2313	*	94041-51EE-2313	*		
290 lbs.	Hard Rubber	99011-51EE-2313	*	94011-51EE-2313	*					

\* Please inquire for additional caster variations.