

# S15 SERIES

## Stainless Steel Stem Casters

Threaded

- Stainless steel forks and hardware
- 2 rows of ball bearings encased in hardened, lubricated raceways
- Swivel uses a zerk fitting and seals to allow for lubrication
- White wheels on request
- Brakes available
- NSF approved caster
- USFDA approved wheels for direct contact with food for human consumption.



Diameter	Tread Width	Wheel Type	Bearing Type	Capacity	Load Height	Swivel Radius	Caster Numbers
							Threaded
4"	1 3/8"	Polyolefin	Plain	300	4 15/16"	3 1/2"	04-TS15-11
	1 3/8"	Polyolefin	Delrin	300			04-TS15-14
	1 3/8"	Polyolefin	S.S. Ball	300			04-TS15-15
	1 3/8"	Mold-On Poly	Delrin	300			04-TS15-24
	1 3/8"	Mold-On Poly	S.S. Ball	300			04-TS15-25
	1 3/8"	Retort	S.S. Bushing	300			04-TS15-121
	1 3/8"	Retort	S.S. Ball	300			04-TS15-125
	1 3/8"	Softie	Delrin	170			04-TS15-154
	1 3/8"	Softie	S.S. Ball	170			04-TS15-155
	1 3/8"	Heateater	S.S. Bushing	300			04-TS15-171
	1 3/8"	Heateater	S.S. Ball	300			04-TS15-175
	1 3/8"	TPR 82A	Delrin	300			04-TS15-194
	1 3/8"	TPR 82A	S.S. Ball	300			04-TS15-195
	1 3/8"	TPR 60A	Delrin	300			04-TS15-224
	1 3/8"	TPR 60A	S.S. Ball	300			04-TS15-225
	1 1/2"	Polyolefin	Plain	300			45-TS15-11
	1 1/2"	Polyolefin	Delrin	300			45-TS15-14
	1 1/2"	Polyolefin	S.S. Ball	300			45-TS15-15
	1 1/2"	Retort	S.S. Bushing	300			45-TS15-121
	1 3/8"	Heateater	S.S. Bushing	300			451-TS15-171

(CONTINUED)

# S15 SERIES

## Stainless Steel Stem Casters

Threaded (CONTINUED)

Diameter	Tread Width	Wheel Type	Bearing Type	Capacity	Load Height	Swivel Radius	Caster Numbers
							Threaded
5"	1 3/8"	Polyolefin	Plain	300	6 1/16"	4"	05-TS15-11
	1 3/8"	Polyolefin	Delrin	300			05-TS15-14
	1 3/8"	Polyolefin	S.S. Ball	300			05-TS15-15
	1 3/8"	Mold-On Poly	Delrin	300			05-TS15-24
	1 3/8"	Mold-On Poly	S.S. Ball	300			05-TS15-25
	1 3/8"	Retort	S.S. Bushing	300			05-TS15-121
	1 3/8"	Polyolefin	S.S. Ball	300			05-TS15-125
	1 3/8"	Softie	Delrin	180			05-TS15-154
	1 3/8"	Softie	S.S. Ball	180			05-TS15-155
	1 3/8"	Heateater	S.S. Bushing	300			05-TS15-171
	1 3/8"	Heateater	S.S. Ball	300			05-TS15-175
	1 3/8"	TPR 82A	Delrin	300			05-TS15-194
	1 3/8"	TPR 82A	S.S. Ball	300			05-TS15-195
	1 1/4"	Mold-On Poly	Delrin	300			05-TS15-204
	1 1/4"	Mold-On Poly	S.S. Ball	300			05-TS15-205
	1 1/4"	TPR 82A	Delrin	300			05-TS15-214
	1 1/4"	TPR 82A	S.S. Ball	300			05-TS15-215
	1 3/8"	TPR 60A	Delrin	300			05-TS15-224
	1 3/8"	TPR 60A	S.S. Ball	300			05-TS15-225
	1 1/4"	TPR 60A	Delrin	300			05-TS15-284
	1 1/4"	TPR 60A	S.S. Ball	300			05-TS15-285
	1 1/4"	Softie	Delrin	180			05-TS15-294
	1 1/4"	Softie	S.S. Ball	180			05-TS15-295
	1 1/2"	Polyolefin	Plain	300			55-TS15-11
	1 1/2"	Polyolefin	Delrin	300			55-TS15-14
1 1/2"	Polyolefin	S.S. Ball	300	55-TS15-15			
1 1/2"	Retort	S.S. Bushing	325	55-TS15-121			
6"	1 3/8"	Polyolefin	Plain	300	7 1/16"	4 1/2"	06-TS15-11
	1 3/8"	Polyolefin	Delrin	300			06-TS15-14
	1 3/8"	Polyolefin	S.S. Ball	300			06-TS15-15
	1 3/8"	Mold-On Poly	Delrin	300			06-TS15-24
	1 3/8"	Mold-On Poly	S.S. Ball	300			06-TS15-25
	1 3/8"	Retort	S.S. Bushing	300			06-TS15-121
	1 3/8"	Retort	S.S. Ball	300			06-TS15-125
	1 3/8"	Softie	Delrin	190			06-TS15-154
	1 3/8"	Softie	S.S. Ball	190			06-TS15-155
	1 3/8"	Heateater	S.S. Bushing	300			06-TS15-171
	1 3/8"	Heateater	S.S. Ball	300			06-TS15-175
	1 3/8"	TPR 82A	Delrin	300			06-TS15-194
	1 3/8"	TPR 82A	S.S. Ball	300			06-TS15-195
	1 3/8"	TPR 60A	Delrin	300			06-TS15-224
	1 3/8"	TPR 60A	S.S. Ball	300			06-TS15-225
	1 1/2"	Polyolefin	Plain	300			65-TS15-11
	1 1/2"	Retort	S.S. Bushing	325			65-TS15-121

### S15 Series Threaded Stems

1/2-13 x 1 1/2

1/2-13 x 2 3/4

# S15 SERIES

## Stainless Steel Stem Casters

Rubber Applicator



AVAILABLE APPLICATORS	
NUMBER	SIZE
9	$\frac{3}{4}$ - $1\frac{1}{16}$ - $2\frac{5}{32}$
11	$\frac{7}{8}$ - $2\frac{9}{32}$
13	$1\frac{5}{16}$ - 1
15	$1\frac{1}{16}$ - $1\frac{1}{8}$
17B	$1\frac{3}{16}$
19A	$1\frac{1}{2}$
19C	$1\frac{3}{8}$
21	$1\frac{3}{4}$ - $1\frac{7}{8}$ - $1\frac{13}{16}$

Diameter	Tread Width	Wheel Type	Bearing Type	Capacity	Swivel Radius	Rubber Applicator	
						Load Height	Number
4"	$1\frac{3}{8}$ "	Polyolefin	Plain	300	$3\frac{1}{2}$ "	$4\frac{15}{16}$ "	04-AS15-11
	$1\frac{3}{8}$ "	Polyolefin	Delrin	300			04-AS15-14
	$1\frac{3}{8}$ "	Polyolefin	S.S. Ball	300			04-AS15-15
	$1\frac{3}{8}$ "	Mold-On Poly	Delrin	300			04-AS15-24
	$1\frac{3}{8}$ "	Mold-On Poly	S.S. Ball	300			04-AS15-25
	$1\frac{3}{8}$ "	Retort	S.S. Bushing	300			04-AS15-121
	$1\frac{3}{8}$ "	Retort	S.S. Ball	300			04-AS15-125
	$1\frac{3}{8}$ "	Softie	Delrin	170			04-AS15-154
	$1\frac{3}{8}$ "	Softie	S.S. Ball	170			04-AS15-155
	$1\frac{3}{8}$ "	Heateater	S.S. Bushing	300			04-AS15-171
	$1\frac{3}{8}$ "	Heateater	S.S. Ball	300			04-AS15-175
	$1\frac{3}{8}$ "	TPR 82A	Delrin	300			04-AS15-194
	$1\frac{3}{8}$ "	TPR 82A	S.S. Ball	300			04-AS15-195
	$1\frac{3}{8}$ "	TPR 60A	Delrin	300			04-AS15-224
	$1\frac{3}{8}$ "	TPR 60A	S.S. Ball	300			04-AS15-225
	$1\frac{1}{2}$ "	Polyolefin	Plain	300			45-AS15-11
	$1\frac{1}{2}$ "	Polyolefin	Delrin	300			45-AS15-14
	$1\frac{1}{2}$ "	Polyolefin	S.S. Ball	300			45-AS15-15
	$1\frac{1}{2}$ "	Retort	S.S. Bushing	300			45-AS15-121
	$1\frac{1}{2}$ "	Heateater	S.S. Bushing	300			451-AS15-171

(CONTINUED)

# S15 SERIES

## Stainless Steel Stem Casters

Rubber Applicator (CONTINUED)

Diameter	Tread Width	Wheel Type	Bearing Type	Capacity	Swivel Radius	Rubber Applicator	
						Load Height	Number
5"	1 3/8"	Polyolefin	Plain	300	4"	6 1/16"	04-AS15-11
	1 3/8"	Polyolefin	Plain	300			05-AS15-11
	1 3/8"	Polyolefin	Delrin	300			05-AS15-14
	1 3/8"	Polyolefin	S.S. Ball	300			05-AS15-15
	1 3/8"	Mold-On Poly	Delrin	300			05-AS15-24
	1 3/8"	Mold-On Poly	S.S. Ball	300			05-AS15-25
	1 3/8"	Retort	S.S. Bushing	300			05-AS15-121
	1 3/8"	Retort	S.S. Ball	300			05-AS15-125
	1 3/8"	Softie	Delrin	180			05-AS15-154
	1 3/8"	Softie	S.S. Ball	180			05-AS15-155
	1 3/8"	Heateater	S.S. Bushing	300			05-AS15-171
	1 3/8"	Heateater	S.S. Ball	300			05-AS15-175
	1 3/8"	TPR 82A	Delrin	300			05-AS15-194
	1 3/8"	TPR 82A	S.S. Ball	300			05-AS15-195
	1 1/4"	Mold-On Poly	Delrin	300			05-AS15-204
	1 1/4"	Mold-On Poly	S.S. Ball	300			05-AS15-205
	1 1/4"	TPR 82A	Delrin	300			05-AS15-214
	1 1/4"	TPR 82A	S.S. Ball	300			05-AS15-215
	1 3/8"	TPR 60A	Delrin	300			05-AS15-224
	1 3/8"	TPR 60A	S.S. Ball	300			05-AS15-225
	1 1/4"	TPR 60A	Delrin	300			05-AS15-284
	1 1/4"	TPR 60A	S.S. Ball	300			05-AS15-285
	1 1/4"	Softie	Delrin	160			05-AS15-294
	1 1/4"	Softie	S.S. Ball	160			05-AS15-295
	1 1/2"	Polyolefin	Plain	300			55-AS15-11
	1 1/2"	Polyolefin	Delrin	300			55-AS15-14
	1 1/2"	Polyolefin	S.S. Ball	300			55-AS15-15
	1 1/2"	Retort	S.S. Bushing	300			55-AS15-121
6"	1 3/8"	Polyolefin	Plain	300	4 1/2"	7 1/16"	06-AS15-11
	1 3/8"	Polyolefin	Delrin	300			06-AS15-14
	1 3/8"	Polyolefin	S.S. Ball	300			06-AS15-15
	1 3/8"	Mold-On Poly	Delrin	300			06-AS15-24
	1 3/8"	Mold-On Poly	S.S. Ball	300			06-AS15-25
	1 3/8"	Retort	S.S. Bushing	300			06-AS15-121
	1 3/8"	Retort	S.S. Ball	300			06-AS15-125
	1 3/8"	Softie	Delrin	190			06-AS15-154
	1 3/8"	Softie	S.S. Ball	190			06-AS15-155
	1 3/8"	Heateater	S.S. Bushing	300			06-AS15-171
	1 3/8"	Heateater	S.S. Ball	300			06-AS15-175
	1 3/8"	TPR 82A	Delrin	300			06-AS15-194
	1 3/8"	TPR 82A	Ball	300			06-AS15-195
	1 3/8"	TPR 60A	Delrin	300			06-AS15-224
	1 3/8"	TPR 60A	S.S. Ball	300			06-AS15-225
	1 1/2"	Polyolefin	Plain	300			65-AS15-11
	1 1/2"	Retort	S.S. Bushing	325			65-AS15-121