

# Wheels

1-800-215-8220

## MonoTech Light Duty



MonoTech wheels are constructed of a special mix of monoprene that rejects almost every type of floor debris and has a high load capacity. Their soft tread durometer allows for maximum shock absorption and cushions the ride to protect your equipment, cargo and floors while reducing noise. They are resistant to most chemicals and oils.

Wheel Diameter	Tread Width	Bearing	Thread Guard	Hub Length	Axle Size	Color Tread/Core	Dynamic Load	Durometer/Shore Scale	Part Number
3"	15/16"	Plain Bore	None	1.01"	1/4"	Grey/Grey	120 lbs.	65A	009001
4"	1"	Plain Bore	None	1.18"	5/16"	Grey/Grey	150 lbs	65A	009003
5"	1"	Plain Bore	None	1.18"	5/16"	Grey/Grey	160 lbs	65A	007315
	1"	Precision	Full	1.18"	5/16"	Grey/Grey	160 lbs	65A	007320

## MonoTech Donut Tread



Wheel Diameter	Tread Width	Bearing	Thread Guard	Hub Length	Axle Size	Color Tread/Core	Dynamic Load	Durometer/Shore Scale	Part Number	Institutional Wheel Code
4"	1-1/4"	Precision Ball	Partial	1-5/8"	3/8"	Grey/Grey	250	65A	009919	DMT(32)
	1-1/4"	Delrin	None	1-1/2"	1/2"	Grey/Grey	250	65A	009907	DMT(11)
5"	1-1/4"	Precision Ball	Partial	1-5/8"	3/8"	Grey/Grey	300	65A	009908	DMT(32)
	1-1/4"	Delrin	None	1-1/2"	1/2"	Grey/Grey	300	65A	009901	DMT(11)
6"	1-1/4"	Precision Ball	Partial	1-5/8"	3/8"	Grey/Grey	325	65A	009904	DMT(32)
	1-1/4"	Delrin	None	1-1/2"	1/2"	Grey/Grey	325	65A	009903	DMT(11)

## MonoTech Flat Tread



Wheel Diameter	Tread Width	Bearing	Thread Guard	Hub Length	Axle Size	Color Tread/Core	Dynamic Load	Durometer/Shore Scale	Part Number	Institutional Wheel Code
3-1/2"	1-1/4"	Precision Ball	Partial	1-5/8"	3/8"	Grey/Grey	250	65A	009916	FMT(32)
	1-1/4"	Delrin	None	1-1/2"	1/2"	Grey/Grey	250	65A	009913	FMT(11)
4"	1-1/4"	Precision Ball	Partial	1-5/8"	3/8"	Grey/Grey	300	65A	009917	FMT(32)
	1-1/4"	Delrin	None	1-1/2"	1/2"	Grey/Grey	300	65A	009914	FMT(11)
5"	1-1/4"	Precision Ball	Partial	1-5/8"	3/8"	Grey/Grey	325	65A	009918	FMT(32)
	1-1/4"	Delrin	None	1-1/2"	1/2"	Grey/Grey	325	65A	009915	FMT(11)

## Thermoplastic Rubber (TPR)



Thermoplastic Rubber (TPR) wheels offer resistance to oils and chemicals and are a great alternative to standard rubber wheels. The tread is mechanically bonded to the core to eliminate separation.

Wheel Diameter	Tread Width	Bearing	Thread Guard	Hub Length	Axle Size	Color Tread/Core	Dynamic Load	Durometer/Shore Scale	Part Number
2"	13/16"	Plain Bore	None	0.90"	1/4"	Grey/Black	80 lbs	40D	007962
	13/16"	Plain Bore	None	0.92"	5/16"	Grey/Grey	80 lbs	40D	618713
2-1/2"	13/16"	Plain Bore	None	0.90"	1/4"	Grey/Black	90 lbs.	40D	007964
3"	13/16"	Plain Bore	None	1.00"	1/4"	Grey/Black	125 lbs	40D	007966
	1-1/4"	Delrin	None	1.5"	3/8"	Grey/Grey	210 lbs	85A	009014
	1-1/4"	Ball Bearing	None	1.625"	3/8"	Grey/Grey	210 lbs	85A	009104
	1-1/4"	Precision	Full	1.57"	3/8"	Grey/Grey	210 lbs	85A	009163
3-1/2"	1-1/4"	Delrin	None	1.5"	3/8"	Grey/Grey	250 lbs	85A	009197
	1-1/4"	Ball Bearing	Partial	1.625"	3/8"	Grey/Grey	250 lbs	85A	009198
4"	15/16"	Plain Bore	None	1.15"	5/16"	Grey/Black	125 lbs	75A	007273
	1-1/4"	Delrin	None	1.5"	3/8"	Grey/Grey	260 lbs	85A	009018
	1-1/4"	Ball Bearing	Partial	1.625"	3/8"	Grey/Grey	260 lbs	85A	009108
	1-1/4"	Precision	Full	1.57"	3/8"	Grey/Grey	260 lbs	85A	009167
5"	1"	Plain Bore	None	1.15"	5/16"	Grey/Black	150 lbs	75A	007313
	1-1/4"	Delrin	None	1.5"	3/8"	Grey/Grey	280 lbs	85A	009022
	1-1/4"	Ball Bearing	Partial	1.625"	3/8"	Grey/Grey	280 lbs	85A	009112
	1-1/4"	Precision	Full	1.59"	3/8"	Grey/Grey	280 lbs	85A	009171
6"	1-1/4"	Precision	Full	1.57"	3/8"	Grey/Grey	300	80-90 A	009899