

Bassick Honcho HS/HR

1-800-215-8220



Features

- Heavy steel, dual ball raceway
- Durable stamped-welded construction
- 2-1/2" wide wheels for increased load handling
- Heavy, staked kingpin
- Sealed upper and lower ball races
- Yellow dichromate finish for added corrosion resistance

Applications

- Power Towed Application
- High Abuse Applications
- Rough floors

Options

Swivel Lock: 4 position swivel lock. To order, add [-SLB] to end of model.

Wheel Selection



Urethane



HS Swivel Top Plate Models

Wheel Dia.	Tread Width	Tread Type	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius	Part Number
6"	2-1/2"	Urethane on Aluminum	Sealed Roller	1750	7-1/2"	4-3/4"	CHS60158YZ-UOA81(BG)
8"	2-1/2"	Urethane on Aluminum	Sealed Roller	1750	9-1/2"	6"	CHS80158YZ-UOA81(BG)
10"	2-1/2"	Urethane on Aluminum	Sealed Roller	1750	11-1/2"	7-1/4"	CHS10158YZ-UOA81(BG)



HR Rigid Top Plate Models

Wheel Dia.	Tread Width	Tread Type	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius	Part Number
6"	2-1/2"	Urethane on Aluminum	Sealed Roller	1750	7-1/2"	N/A	CHR60158YZ-UOA81(BG)
8"	2-1/2"	Urethane on Aluminum	Sealed Roller	1750	9-1/2"	N/A	CHR80158YZ-UOA81(BG)
10"	2-1/2"	Urethane on Aluminum	Sealed Roller	1750	11-1/2"	N/A	CHR10158YZ-UOA81(BG)

Swivel Lock
Add [-SLB] at end of model.

▲ 158

