

Institutional Pneumatic



Features

- Pneumatic wheels absorb shock for a smoother ride
- Reduces vibration to protect sensitive equipment and cargo
- Rolls over floor cracks, obstacles and uneven surfaces with ease
- Easy access inflation valve stem

Applications

- Hospital Equipment
- Utility Carts
- Store Fixtures
- Institutional Equipment
- Electronics Equipment
- Office Equipment
- Food Service

Options

Brakes: Tread Lock
Threaded Stem Washer
Wrench: Holds caster in place while assembling to unit (see page 73). To order specify: [Wrench FE GS GT ZH].

Wheel Selection



Grey Pneumatic tread on metallic grey polyolefin core (90 PSI)



Black Pneumatic tread on metallic grey polyolefin core (90 PSI)



Tread Lock Brake Add [TB] at end of model.

Threaded Stem Models

Wheel Dia.	Tread Width	Tread Type	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius	Part Number	Fastening Selection
6"	1-1/4"	Grey Pneumatic	Ball	150	7-1/8"	4-1/2"	PGS60_ZN-PNU21(GG)	741, 748
	1-1/4"	Black Pneumatic	Ball	150	7-1/8"	4-1/2"	PGS60_ZN-PNU21(KG)	741, 748

Recommended pneumatic tire pressure is 90 PSI.

741 748

To order include fastener code. Example: PGS30741ZN-PNU21(GG).



Tread Lock Brake Add [TB] at end of model.

Grip Ring Stem Models

Wheel Dia.	Tread Width	Tread Type	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius	Part Number	Fastening Selection
6"	1-1/4"	Grey Pneumatic	Ball	150	7-1/8"	4-1/2"	PGS60Z73ZN-PNU21(GG)	273
	1-1/4"	Black Pneumatic	Ball	150	7-1/8"	4-1/2"	PGS60Z73ZN-PNU21(KG)	273

Recommended pneumatic tire pressure is 90 PSI.

273

1-7/16"
7/16"
Brass Band