

Wheels

1-800-215-8220

Solid Polyolefin



Regent/
Monarch

Bassick
00

Polyolefin wheels are the most economical wheel option. Their high-impact, lightweight construction is resistant to most chemicals and oils.

Wheel Diameter	Tread Width	Bearing	Hub Length	Axle Size	Color Tread/Core	Dynamic Load	Durometer/Shore Scale	Part Number
2"	3/4"	Plain	.90"	1/4"	Black	100 lbs	70D	007956
	3/4"	Plain	.921	5/16"	Black	100 lbs	70D	618712
	1-13/16"	Plain	1.85	5/16"	Black	300 lbs	70D	618714

Spherical



Baron

Solid, spherical construction designed for efficient mobility.

Wheel Diameter	Tread Type	Hub Length	Axle Size	Color Tread/Core	Dynamic Load	Durometer/Shore Scale	Part Number
1-5/8"	Soft Rubber	1.52"	7/32"	Black	75 lbs	75A	006522
2"	Polyolefin	1.98"	1/4"	Black	100 lbs	70D	006520

Vipor



Regent/
Monarch

Institutional

Vipor Wheels are constructed of a special material that is highly resistant to most chemicals and oils. The high-tech transparent look enhances your equipment's appearance.

Wheel Diameter	Tread Width	Bearing	Hub Length	Axle Size	Color Tread/Core	Dynamic Load	Durometer/Shore Scale	Part Number
2"	7/8"	Plain	1"	1/4"	Clear/Grey	80 lbs	90A	001920
3"	15/16"	Plain	.99"	1/4"	Clear/Grey	120 lbs	85-90A	001899
6"	1-1/4"	Ball	1.59"	3/8"	Clear/Grey	300 lbs	85-95A	009256

Pneumatic



Institutional

Pneumatic wheels absorb shock and reduce vibration to protect sensitive equipment and cargo by providing a smoother ride. The air cushioned tread rolls over floor cracks, obstacles and uneven surfaces with ease.

Wheel Diameter	Tread Width	Bearing	Hub Length	Axle Size	Color Tread/Core	Dynamic Load	Tire Pressure	Part Number
6"	1-1/4"	Ball Bearing	1.57	3/8"	Grey/Grey	150 lbs	90 PSI	006038
	1-1/4"	Ball Bearing	1.57	3/8"	Black/Grey	150 lbs	90 PSI	006006

No-Matic



Institutional

Pneumatic look and feel without the hassles of air pressure maintenance and flat tires! This maintenance-free caster wheel has similar cushion ride as pneumatic caster wheels.

Wheel Diameter	Tread Width	Bearing	Hub Length	Axle Size	Color Tread/Core	Dynamic Load	Durometer/Shore Scale	Part Number
6"	1-1/4"	Ball Bearing	1.57	3/8"	Grey/Grey	150 lbs	70A	009923
	1-1/4"	Ball Bearing	1.57	3/8"	Black/Grey	150 lbs	70A	009922

Phenolic



Bassick
Honcho

Phenolic Wheels have high load capacity, are impact resistant and easy rolling. These wheels are non-marking and recommended for hand-pushed or power-towed applications on hard smooth floors or carpeting.

Wheel Diameter	Tread Width	Bearing	Hub Length	Axle Size	Color Tread/Core	Dynamic Load	Durometer/Shore Scale	Part Number
3"	1-5/16"	Roller	0.156"	3/8"*	Black	400 lbs	95D	615633
	1-13/16"	Roller	1.94"	3/8"*	Black	900 lbs	95D	615529
4"	1-5/8"	Roller	1.88"	3/8"*	Black	600 lbs	95D	617898
4"	2"	Sealed Roller	2.38"	1/2"*	Black	800 lbs	95D	617937
5"	2"	Sealed Roller	2.38"	1/2"*	Black	1250 lbs	95D	618012
6"	2"	Sealed Roller	2.38"	1/2"*	Black	1500 lbs	95D	618095
8"	2"	Sealed Roller	2.38"	1/2"*	Black	1500 lbs	95D	618156

*Requires spanner