



SCAFFOLD CASTERS

TP8900 SERIES / CAPACITY TO 800 LBS



- “Dual-Unison” locking system engages both wheel brake and swivel lock simultaneously, and is hand or foot operated.
- When fully locked, will not disengage.
- Thread guards standard : Helps keep out dirt, dust, and other caster-hazardous materials that affect the wheel bearing.
- It’s called a scaffold caster, but it’s also ideally suited for floodlight stands, motion picture equipment and other movable work platforms that need to roll and stay put.
- The most popular stem is standard, but inquiries on other sizes are welcome.
- Zerk fittings provided in the axle and swivel for lubrication.

							MODEL No SWIVEL
6 (152.4)	2	Rubber/Cast Iron Polyurethane	Roller Roller	410 700	7-1/2	4-31/32	TP8960- ** -RCI-TG TP8960- ** -PCI-TG
8 (203.2)	2	Rubber/Cast Iron Polyurethane	Roller Roller	500 800	9-1/2	6-1/4	TP8980- ** -RCI-TG TP8980- ** -PCI-TG

FASTENINGS FOR SERIES 8900

TYPE	CODE	SIZE
Top Plate	01	Overall 5 × 5-1/2
		Hole Spacing Slotted 4-1/8 × 4-1/2
		Attaching Bolt Size 7/16
Round Plain Stem	31	1-3/8 × 4 with 1/2 cross drilled hole drilled 2-1/2 up from base on center
	32	1-7/16 × 4 with 3/8 cross drilled hole drilled 2-1/2 up from base on center
	33	1-1/4 × 4 with 1/2 cross drilled hole drilled 2-1/2 up from base on center

