

# Five-Inch Wheel Diameter Cart Casters

MADE IN U.S.A.



## STANDARD FEATURES

### SERIES 1F08 AND 1F00

- Light-medium duty applications.
- Double row swivel construction.
- Zinc-plated finish for corrosion resistance and appearance.
- Heat treat hardened and factory lubricated swivel raceways.
- 5/16" diameter rivet axle.

### SERIES 1F38 AND 1F30

- Medium duty applications.
- Double row swivel construction.
- Zinc-plated finish for corrosion resistance and appearance.
- Heat treat hardened and factory lubricated swivel raceways.
- 3/8" diameter nut and bolt axle.



190 to 280 lb. capacity  
1 1/4" wheel tread width

**SERIES 1F08**  
Double Row Swivel Plate Caster



**SERIES 1F00**  
One-piece Rigid Plate Caster

Top Plate Size  
Overall Size: 2-3/4" x 3-3/4"  
Hole Spacing: 1-3/4" x 3"  
Hole Diameter: 11/32"  
Bolt Diameter: 5/16"

OPTIONS: Consult Factory  
Side mount pinch type wheel brake.  
(Swivel casters only)  
5/16" diameter nut and bolt axle.



350 to 375 lb. capacity  
2" wheel tread width

**SERIES 1F38**  
Double Row Swivel Plate Caster



**SERIES 1F30**  
One-piece Rigid Plate Caster

Top Plate Size  
Overall Size: 2-3/4" x 3-3/4"  
Hole Spacing: 1-3/4" x 3"  
Hole Diameter: 11/32"  
Bolt Diameter: 5/16"

OPTIONS: Consult Factory  
Side mount pinch type wheel brake.  
(Swivel casters only)  
Economical 3/8" diameter rivet axle.

## Wheel Types



**Cushionex Supreme**  
Black soft rubber tread molded to black hard rubber core.



**Spartan Supreme**  
Black hard rubber tread molded to black hard rubber core.



**Poly II Urethane**  
Red polyurethane tread molded to light gray polypropylene core.



**Poly II Rubber**  
Black thermoplastic rubber thread molded to light gray polypropylene core.



**Durafoam (Solid)**  
Black molded polypropylene.



**Duratex**  
Black phenolic resin reinforced with macerated fabric.

A	Approximate	Caster	Wheel	B	C	Approximate	Swivel Caster	Rigid Caster
Wheel Dia. (inches)	Tread Width (inches)	Capacity (pounds)	Bearing Type	Height (inches)	Swivel Radius (inches)	Weight (pounds)	Part No.	Part No.
<b>CUSHIONEX SUPREME WHEEL</b>								
5	1-1/4	190	Delrin	6	3-7/8	2-1/2	1F0855004000100	1F0055004000100
5	2	350	Delrin	6	4-3-16	4	1F3805004000100	1F3005004000100
5	2	350	Roller	6	4-3/16	3-3/4	1F3805404000100	1F3005404000100
<b>POLY II RUBBER WHEEL</b>								
5	2	350	Delrin	6	4-3/16	2-3/4	1F3805B26000100	1F3005B26000100
<b>SPARTAN SUPREME WHEEL</b>								
5	1-1/4	280	Delrin	6	3-7/8	2-1/2	1F0855009000100	1F0055009000100
5	2	375	Delrin	6	4-3/16	3-3/4	1F3805009000100	1F3005009000100
<b>DURAFOAM WHEEL</b>								
5	1-1/4	280	Plain	6	3-7/8	2	1F0855027000100	1F0055027000100
5	2	375	Plain	6	4-3/16	2-3/4	1F3805027000100	1F3005027000100
<b>POLY II URETHANE WHEEL</b>								
5	2	375	Delrin	6	4-3/16	2-3/4	1F3805B25000100	1F3005B25000100
<b>DURATEX WHEEL</b>								
5	2	375	Roller	6	4-3/16	3-3/4	1F3805438000100	1F3005438000100

